

253 mm

197 mm

PRODUCT-DETAILS

**Product Net Width** 

**Product Net Height** 

## **OSM50GF4N1M230C**OSM50GF4N1M230C MOTORIZED SWITCHFUSE



General Information	
Extended Product Type	OSM50GF4N1M230C
Product ID	1SCA118871R1001
EAN	6417019505213
Catalog Description	OSM50GF4N1M230C MOTORIZED SWITCHFUSE
Long Description	Including a handle for manual operation, including protected tunnel terminals, male connectors for control circuit and a handle and spare fuse storage clip.
Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311029M0203
Dimensions	

OSM50GF4N1M230C 2

Product Net Depth / Length	138 mm
Product Net Weight	4.87 kg 10.74 lb

Technical	
Rated Operational	(380 415 V) 50 A
Current AC-21A (I <sub>e</sub> )	(500 V) 50 A
	(690 V) 50 A
Rated Operational	(500 V) 50 A
Current AC-22A (I <sub>e</sub> )	(380 415 V) 50 A (690 V) 50 A
Rated Operational	(380 415 V) 50 A
Current AC-23A (I <sub>e</sub> )	(500 V) 50 A
	(690 V) 50 A
Rated Operational Power	(380 415 V) 22 kW
AC-23A (P <sub>e</sub> )	(500 V) 30 kW
	(690 V) 37 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 50 A
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	12 KV
)	
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	1000 V
	for 1 o 2 F biles man are more
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 2.5 kiloampere rms
Rated Conditional Short- Circuit Current (I <sub>nc</sub> )	(690 V) 80 kA
Motor Operational Voltage	220 240 V AC
Power Loss	at Rated Operating Conditions per Pole 2.5 W
Pollution Degree	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Left Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	04 (Left Side)
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	Top in Bottom out, Bottom in Top out
Fuse Size	14X51
Fuse System	NFC
Operating Mode	Motor operated and manually from the front
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Screw Terminals
Fuse Type	NFC NFC
	NIC

## Environmental ISCC311002D0201

## **Certificates and Declarations (Document Number)**

Environmental Information

Information

1SCC311002D0201

Instructions and 1SCC311029M0203 Manuals

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	328 mm
	12.91 in
Package Level 1 Depth /	365 mm
Length	14.37 in
Package Level 1 Height	260 mm
	10.24 in
Package Level 1 Gross	5.95 kg
Weight	13.12 lb
Package Level 1 EAN	6417019505213

Classifications	
Object Classification Code	Q
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Motorized Switch Fuses

