

PRODUCT-DETAILS

OT2000EM03P

OT2000EM03P SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT2000EM03P
Product ID	1SCA118939R1001
EAN	6417019506197
Catalog Description	OT2000EM03P SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, horizontally base mounted earthing switch with black IP65 handle and shaft, terminal bolt kit included

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301077M0204
Mechanical Drawings	1SCC301961F0001 1SCC301960F0001

Dimensions

Product Net Width	487.5 mm
Product Net Height	376.5 mm
Product Net Depth / Length	234 mm
Product Net Weight	26.3 kg 58 lb

Technical

Rated Operational Current AC-21B (I_e)	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Rated Operational Current AC-22B (I_e)	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 2000 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 176 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 55 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	03 (Left Side) Mechanism turned 90 degrees
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50...75 N·m
Mechanical Durability	6000
Lock Type	Yes
Utilization	Earthing Switch Use

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301176D2702
DNV GL Certificate	1SCC301184D0203
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301077M0204
RoHS Information	1SCC301149D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	400 mm 15.7 in
Package Level 1 Depth / Length	630 mm 24.8 in
Package Level 1 Height	300 mm 11.8 in
Package Level 1 Gross Weight	28.4 kg 62.6 lb
Package Level 1 EAN	6417019506197

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3600198

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

