

PRODUCT-DETAILS

OT1000EM03 OT1000EM03 SWITCH-DISCONNECTOR



General Information		
Extended Product Type	OT1000EM03	
Product ID	1SCA119004R1001	
EAN	6417019505763	
Catalog Description	OT1000EM03 SWITCH-DISCONNECTOR	
Long Description	3-pole, front operated, horizontally base mounted earthing switch, handle and shaft are no included, terminal bolt kit include	
Ordering		
Minimum Order Quantity	1 piece	
Customs Tariff Number	85365080	
Country of Origin	Finland (FI)	
Popular Downloads		
Data Sheet, Technical Information	1SCC301020C0201	
Instructions and Manuals	1SCC301076M0204	
Mechanical Drawings	1SCC301953F0001 1SCC301952F0001	

Dimensions	
Product Net Width	349.5 mm
Product Net Height	306 mm
Product Net Depth / Length	234 mm
Product Net Weight	15.4 kg
Technical	
Rated Operational Current AC-22A (I _e)	(380 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-23A (I _e)	(380 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P _e)	(400 415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 1000 A
Conventional Thermal Current (I _{the})	Fully Enclosed 1000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 110 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 50 kA
Power Loss	at Rated Operating Conditions per Pole 19 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	03 (Left Side) Mechanism turned 90 degrees
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 5075 N·m
Mechanical Durability	6000
Lock Type	No
Utilization	Earthing Switch Use

Environmental	
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202
Certificates and Declarations (Document Numb	per)
Declaration of Conformity - CE	1SCC301155D2704
DNV GL Certificate	1SCC301184D0203
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301076M0204
RoHS Information	1SCC301149D0203
Package Level 1 Units	box 1 piece
Container Information	
Package Level 1 Width	400 mm
Package Level 1 Depth / Length	400 mm
Package Level 1 Height	325 mm
Package Level 1 Gross Weight	17 kg
Package Level 1 EAN	6417019505763
Classifications	
Object Classification Code	C
ETIM 5	EC000216 - Switch disconnecto
ETHIN 3	
ETIM 6	EC000216 - Switch disconnecto

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

WEEE Category

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Disconnectors

OT1000EM03 4

