

PRODUCT-DETAILS

EOT30U4S4-P

EOT30U4S4-P Enclosed Disconnect Switch



General Information

Extended Product Type	EOT30U4S4-P
Product ID	1SCA119880R1001
EAN	6417019514826
Catalog Description	EOT30U4S4-P Enclosed Disconnect Switch
Long Description	Enclosed Switch Disconnecter, 4-p. Max. Horse power rating at three phase 480V 20HP. General purpose current rating 30A. Steel sheet enclosure, NEMA Type 4/4X Watertight, Pistol handle. Interlocked cover. Defeatable interlocking.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Mexico (MX)

Popular Downloads

Data Sheet, Technical Information	1SCC340016C0201
Instructions and Manuals	1SCC340019M0202
Mechanical Drawings	EOTK4241510PBL.stp

Dimensions

Product Net Width	159.5 mm 6.28 in
Product Net Height	241.3 mm 9.5 in
Product Net Depth / Length	108.7 mm 4.28 in
Product Net Weight	2.6 kg 4.63 lb

Technical

Rated Operational Current AC-22A (I_g)	(380 ... 415 V) 45 A (690 V) 45 A
Rated Operational Current AC-23A (I_g)	(380 ... 415 V) 30 A (690 V) 20 A
Conventional Thermal Current (I_{the})	30 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 3.6 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 2.5 kA
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3 / UL 98
Number of Poles	4
Connecting Capacity Main Circuit	Screw Clamp 0.75...10 mm ² Screw Clamp / PE Terminal 1pcs, 0.5...16 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	Blank / Blank
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Type	NEMA Type 4/4X Watertight
Enclosure Material	Stainless steel
Mounted Auxiliary Contacts	0 NO, 0 NC
Terminal Type	Screw Terminals
Mechanical Durability	20000

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Horsepower Rating UL/CSA	(220 ... 240 V AC) Three Phase 10 Hp (480 V AC) 20 Hp (600 V AC) 30 Hp
Ampere Rating UL/CSA	30 A
Tightening Torque UL/CSA	Main Circuit 7 in-lb

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1CC340035D2701
Instructions and Manuals	1SCC340019M0202

Container Information		
Package Level 1 Units		1 piece
Package Level 1 Width		242 mm
Package Level 1 Depth / Length		303 mm
Package Level 1 Height		192 mm
Package Level 1 Gross Weight		2.6 kg 5.73 lb
Package Level 1 EAN		6417019514826

Classifications		
Object Classification Code		Q
ETIM 5	EC000216 - Switch disconnect	
ETIM 6	EC000216 - Switch disconnect	
ETIM 7	EC000216 - Switch disconnect	
UNSPSC		39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Categories	
Low Voltage Products and Systems → Enclosed Switches → Enclosed Disconnect Switches	

