

PRODUCT-DETAILS

OS160GD12BB

OS160GD12BB SPECIAL CONNECTED SWITCH FUSE



| General Information | |
|-----------------------|---|
| Extended Product Type | OS160GD12BB |
| Product ID | 1SCA120751R1001 |
| EAN | 6417019521893 |
| Catalog Description | OS160GD12BB SPECIAL CONNECTED SWITCH FUSE |
| Long Description | Switch Fuses,Front Operated,3-pole,12 (Between the Poles),DIN,000,00,Handle and shaft not included, |

| Ordering | |
|-----------------------|--------------|
| Customs Tariff Number | 85365080 |
| Country of Origin | Finland (FI) |

| Popular Downloads | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC311140D0201 |
| Instructions and Manuals | 1SCC110037M0206 |

| Dimensions | |
|--------------------|--------|
| Product Net Width | 215 mm |
| Product Net Height | 144 mm |

| Product Net Depth / Length | 167 mm |
|-------------------------------|---------|
| Product Net Weight | 1.56 kg |

| Technical | |
|--|--|
| Rated Operational | (500 V) 160 A |
| Current AC-21A (I _e) | (690 V) 160 A |
| Rated Operational Current AC-22A (I _e) | (500 V) 160 A (690 V) 160 A |
| Rated Operational Current AC-23A (I _e) | (500 V) 160 A (690 V) 160 A |
| Rated Operational Power AC-23A (P _e) | (220 240 V) 45 kW (400 V) 75 kW (415 V) 75 kW (500 V) 90 kW (690 V) 132 kW |
| Conventional Free-air Thermal Current (I _{th}) | q = 40 °C 160 A |
| Conventional Thermal Current (I _{the}) | Fully Enclosed 160 A |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Rated Insulation Voltage (Ui) | 1000 V |
| Rated Operational Voltage | 500 V |
| Rated Short-time Withstand Current (I _{cw}) | for 1 s 5 kiloampere rms |
| Rated Conditional Short- Circuit Current (I _{nc}) | (690 V) 80 kA |
| Power Loss | at Rated Operating Conditions per Pole 12 W |
| Pollution Degree | 3 |
| Handle Type | Handle and shaft not included |
| Switches Operating Mechanism | 12 (Between the Poles) |
| Position of Line Terminals | Back In - Back Out |
| Fuse Size | 000,00 |
| Fuse System | DIN |
| Operating Mode | Front Operated |
| Standards | IEC 60947-3 |
| Mounting Type | Base mounting |
| Number of Poles | 3 |
| Terminal Type | Lug terminals |
| Terminal Width | 20 mm |
| Tightening Torque | 15 22 N·m |
| Fuse Type | DIN |

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

| Certificates and Declarations (Document Number) | |
|---|-----------------|
| Declaration of Conformity - CE | 1SCC311140D2703 |
| DNV GL Certificate | 1SCC311125D0203 |
| EAC Certificate | EAC |

 ${\tt OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pd}$

| Instructions and Manuals | 1SCC110037M0206 |
|-----------------------------|-----------------|
| RoHS Information | 1SCC311140D2703 |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 210 mm |
| Package Level 1 Depth / Length | 236 mm |
| Package Level 1 Height | 163 mm |
| Package Level 1 Gross Weight | 2.2 kg |
| Package Level 1 EAN | 6417019521893 |

| Classifications | |
|-------------------------------|--|
| Object Classification Code | Q |
| ETIM 4 | EC001040 - Fuse switch disconnector |
| ETIM 5 | EC001040 - Fuse switch disconnector |
| ETIM 6 | EC001040 - Fuse switch disconnector |
| ETIM 7 | EC001040 - Fuse switch disconnector |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Switch Fuses

