

PRODUCT-DETAILS

OTM630E2CM230V

OTM630E2CM230V MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM630E2CM230V
Product ID	1SCA121268R1001
EAN	6417019525297
Catalog Description	OTM630E2CM230V MOTORIZED C/O SWITCH
Long Description	OTM630E2CM230V MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

Dimensions	
Product Net Width	346 mm
Product Net Height	250 mm

Product Net Depth / Length	299 mm
Product Net Weight	10.3 kg 22.7 lb

Technical	
Rated Operational Current AC-21A (I _e)	(380 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A (I _e)	(380 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-31B (I _e)	(380 415 V) 630 A
Rated Operational Current AC-33B (I _e)	(380 415 V) 630 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 630 A
Conventional Thermal Current (I _{the})	Fully Enclosed 630 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 20 kiloampere rms
Motor Operational Voltage	220 240 V AC
Power Loss	25 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	2
Degree of Protection	Front IP20
Transition Type	Open

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	N/A
Instructions and Manuals	1SCC303002M0204

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	310 mm
Package Level 1 Depth / Length	560 mm

OTM630E2CM230V 3

Package Level 1 Height	330 mm
Package Level 1 Gross Weight	14.26 kg
Package Level 1 EAN	6417019525297

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ Change-over\ Switches$

