

PRODUCT-DETAILS

SWITCH

OTM1600E2CM230VOTM1600E2CM230V MOTORIZED C/O



General Information	
Extended Product Type	OTM1600E2CM230V
Product ID	1SCA121280R1001
EAN	6417019525334
Catalog Description	OTM1600E2CM230V MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)
Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201

Dimensions	
Product Net Width	427 mm

Product Net Height	372 mm
Product Net Depth / Length	372 mm
Product Net Weight	37.11 kg 81.81 lb

Technical	
Rated Operational Current AC-21A (I _e)	(380 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-22A (I _e)	(380 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-31B (I _e)	(380 415 V) 1600 A
Rated Operational Current AC-33B (I _e)	(380 415 V) 1000 A
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 1600 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U ₁)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 50 kiloampere rms
Motor Operational Voltage	220 240 V AC
Power Loss	48 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	2
Degree of Protection	Front IP20
Transition Type	Open

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	N/A
Instructions and Manuals	1SCC303002M0204

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	394 mm
	15.51 in
Package Level 1 Depth /	534 mm
Length	21.02 in

OTM1600E2CM230V 3

Package Level 1 Height	368 mm 14.49 in
Package Level 1 Gross	39.5 kg
Weight	87.08 lb
Package Level 1 EAN	6417019525334

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ Change-over\ Switches$

