

PRODUCT-DETAILS

## **OS160GB03N3**OS160GB03N3 SWITCH FUSE



<b>General Information</b>	
Extended Product Type	OS160GB03N3
Product ID	1SCA122009R1001
EAN	6417019530246
Catalog Description	OS160GB03N3 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,03 (Left Side),British Standard,A2-A4,Handle and shaft not included,Detachable Neutral Link Integrated Into the Mechanism

Ordering	
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311137D2703
Instructions and Manuals	1SCC110037M0206

Dimensions	
Product Net Width	147 mm
Product Net Height	140 mm

Product Net Depth /	115 mm
Length	
Product Net Weight	2.08 kg
	4.59 lb

Technical	
Rated Operational	(500 V) 160 A
Current AC-21A (I <sub>e</sub> )	(690 V) 160 A
Rated Operational Current AC-22A (I <sub>e</sub> )	(500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(220 240 V) 45 kW (400 V) 75 kW (415 V) 75 kW (500 V) 90 kW (690 V) 132 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 160 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Rated Insulation Voltage (U <sub>1</sub> )	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 5 kiloampere rms
Rated Conditional Short- Circuit Current (I <sub>nc</sub> )	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 12 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Type	Detachable Neutral Link Integrated Into the Mechanism
Switches Operating Mechanism	03 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	A2-A4
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Special Functions	Detachable Neutral
Mounting Type	Base mounting
Number of Poles	3
Terminal Type	Lug terminals
Terminal Width	20 mm
Tightening Torque	15 22 N·m
	BS

## **Environmental**

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## **Certificates and Declarations (Document Number)**

CCC Certificate CCC OS100-160G\_ 2015.pdf

Declaration of Conformity - CE	1SCC311137D2703
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSMpd f
Instructions and Manuals	1SCC110037M0206
RoHS Information	1SCC311137D2703

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	172 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Height	144 mm
Package Level 1 Gross Weight	2.34 kg 5.16 lb
Package Level 1 EAN	6417019530246

Classifications	
Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Fuses

