

PRODUCT-DETAILS

OT160EV11P

OT160EV11P SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT160EV11P
Product ID	1SCA122710R1001
EAN	6417019536323
Catalog Description	OT160EV11P SWITCH-DISCONNECTOR
Long Description	2-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220
Mechanical Drawings	1SCC301226F0001 1SCC301225F0001 OT200-250E11.stp

Dimensions

Product Net Width	150 mm
Product Net Height	115.5 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.1 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A (1000 V) 200 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 160 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 48 kW (400 ... 415 V) 88 kW (500 V) 112 kW (690 V) 144 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 200 A
Conventional Thermal Current (I_{the})	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 30 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 3.2 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 11 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	2

Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 15...22 N·m
Mechanical Durability	20000
Lock Type	Yes

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301131D2705
DNV GL Certificate	1SCC301174D0204
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301031M0220
RoHS Information	1SCC301149D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	160 mm
Package Level 1 Depth / Length	172 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	6417019536323

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

