

PRODUCT-DETAILS

## **OT250E03YP**

## OT250E03YP BY-PASS SWITCH



General Information	
Extended Product Type	OT250E03YP
Product ID	1SCA123553R1001
EAN	6417019543376
Catalog Description	OT250E03YP BY-PASS SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

Dimensions	
Product Net Width	194 mm
Product Net Height	150 mm
Product Net Depth / Length	236 mm
Product Net Weight	5.23 kg
-	11.53 lb

Technical	
Rated Operational Current AC-21A (I <sub>e</sub> )	(380 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(380 415 V) 140 kW (500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 250 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (Ui)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 8 kiloampere rms
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC301194D0202
Instructions and Manuals	1SCC301080M0003

## **Container Information**

Package Level 1 Units	1 piece
Package Level 1 Width	175 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Height	350 mm
Package Level 1 Gross Weight	5.74 kg 12.65 lb
Package Level 1 EAN	6417019543376

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ bypass\ switches$ 

