

PRODUCT-DETAILS

OT400E12YP

OT400E12YP BY-PASS SWITCH



General Information

Extended Product Type	OT400E12YP
Product ID	1SCA123584R1001
EAN	6417019543680
Catalog Description	OT400E12YP BY-PASS SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

Dimensions

Product Net Width	240 mm
Product Net Height	185 mm
Product Net Depth / Length	306 mm
Product Net Weight	11.51 kg 25.38 lb

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 400 A
Conventional Thermal Current (I_{the})	Fully Enclosed 400 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 15 kiloampere rms
Power Loss	10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301195D0202
Instructions and Manuals	1SCC301080M0003

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	265 mm 10.43 in
Package Level 1 Depth / Length	375 mm 14.76 in
Package Level 1 Height	330 mm 12.99 in
Package Level 1 Gross Weight	11.93 kg 26.3 lb
Package Level 1 EAN	6417019543680

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122217
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual bypass switches

