


## PRODUCT-DETAILS

# OTDC200E02

## OTDC200E02 DC Switch-disconnector



### General Information

|                       |                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OTDC200E02                                                                                                                                       |
| Product ID            | 1SCA123687R1001                                                                                                                                  |
| EAN                   | 6417019544618                                                                                                                                    |
| Catalog Description   | OTDC200E02 DC Switch-disconnector                                                                                                                |
| Long Description      | OTDC200E02 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, IEC 1000 VDC 200 A |

### Ordering

|                        |                          |
|------------------------|--------------------------|
| Minimum Order Quantity | 1 piece                  |
| Customs Tariff Number  | 85363090                 |
| Last Ordering Date     | 2021-11-30 All Countries |
| Country of Origin      | Finland (FI)             |

### Popular Downloads

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| Data Sheet, Technical Information | 1SCC301022C0201                                          |
| Instructions and Manuals          | 1SCC301081M0206                                          |
| Mechanical Drawings               | OTDC100_250E02.igs<br>1SCC307579F0201<br>1SCC307580F0201 |

## Dimensions

|                               |                   |
|-------------------------------|-------------------|
| Product Frame Size            | S                 |
| Product Net Width             | 113 mm<br>4.4 in  |
| Product Net Height            | 262 mm<br>10.3 in |
| Product Net Depth /<br>Length | 90.5 mm<br>3.6 in |
| Product Net Weight            | 1.3 kg<br>2.8 lb  |

## Technical

|                                                       |                                                                                               |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Connection Configuration                              | Single circuit 2a, 2b                                                                         |
| Rated Operational Current<br>DC-21B ( $I_e$ )         | (1000 V) 200 A                                                                                |
| Conventional Free-air<br>Thermal Current ( $I_{th}$ ) | 200 A                                                                                         |
| Conventional Thermal<br>Current ( $I_{the}$ )         | Fully Enclosed 200 A                                                                          |
| Rated Impulse Withstand<br>Voltage ( $U_{imp}$ )      | 12 kV                                                                                         |
| Rated Insulation Voltage<br>( $U_i$ )                 | 1500 V                                                                                        |
| Rated Operational Voltage                             | 1000 V                                                                                        |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ )   | (1000 V DC) 10 kA                                                                             |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )    | (1000 V DC) 10 kA<br>for 1 s 5 kA<br>for 0.1 s 10 kA                                          |
| Power Loss                                            | at Rated Operating Conditions per Pole 6 W                                                    |
| Pollution Degree                                      | 3                                                                                             |
| Handle Type                                           | Handle and shaft not included                                                                 |
| Shaft Diameter                                        | 6 mm<br>0.24 in                                                                               |
| Switches Operating<br>Mechanism                       | Mechanism at the End of the Switch<br>02 (Left Side)                                          |
| Position of Line Terminals                            | Top In - Bottom Out<br>Bottom In - Top Out                                                    |
| Operating Mode                                        | Front Operated                                                                                |
| Standards                                             | IEC 60947-1, -3                                                                               |
| Special Functions                                     | No                                                                                            |
| Mounting Type                                         | Base mounting                                                                                 |
| Number of Circuits                                    | 1                                                                                             |
| Number of Poles                                       | 2                                                                                             |
| Degree of Protection                                  | Front IP20                                                                                    |
| Terminal Type                                         | Lug terminals                                                                                 |
| Terminal Width                                        | 19.5 mm<br>0.77 in                                                                            |
| Tightening Torque                                     | Cable Lug 15...22 N·m                                                                         |
| Utilization                                           | Photovoltaic                                                                                  |
| Utilization Category                                  | Switching of resistive loads, including moderate overloads - occasional<br>actuation (DC-21B) |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Environmental Information

NA

---

**Certificates and Declarations (Document Number)**


---

|                                   |                     |
|-----------------------------------|---------------------|
| CCC Certificate                   | CQC2013010302611671 |
| Declaration of Conformity<br>- CE | 1SCC301201D2703     |
| DNV GL Certificate                | 1SCC301231D0201     |
| Environmental Information         | NA                  |
| Instructions and Manuals          | 1SCC301081M0206     |
| RoHS Information                  | 1SCC301201D2703     |

---



---

**Container Information**


---

|                                   |                  |
|-----------------------------------|------------------|
| Package Level 1 Units             | box 1 piece      |
| Package Level 1 Width             | 210 mm<br>8.3 in |
| Package Level 1 Depth /<br>Length | 210 mm<br>8.3 in |
| Package Level 1 Height            | 150 mm<br>5.9 in |
| Package Level 1 Gross<br>Weight   | 1.4 kg<br>3.2 lb |
| Package Level 1 EAN               | 6417019544618    |

---



---

**Classifications**


---

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)         | 3601597                                                    |

---



---

**Categories**


---

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

