

PRODUCT-DETAILS

OTDC16FT4

OTDC16FT4 DC Switch-disconnector



General Information

Extended Product Type	OTDC16FT4
Product ID	1SCA123841R1001
EAN	6417019545608
Catalog Description	OTDC16FT4 DC Switch-disconnector
Long Description	OTDC16FT4 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Door mounting, IEC 660 VDC 16 A double circuit, IEC 1000 VDC 10 A double circuit

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Estonia (EE)

Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301079M0206
Mechanical Drawings	OTDC16-32FT4_palikkamalli.igs 1SCC307019F0002

1SCC307020F0002

Dimensions

Product Frame Size	XS
Product Net Width	52.5 mm 2.1 in
Product Net Height	69 mm 2.7 in
Product Net Depth / Length	87 mm 3.4 in
Product Net Weight	0.2 kg 0.5 lb

Technical

Rated Operational Current DC-21B (I_e)	(660 V) 16 A (1000 V) 10 A
Conventional Free-air Thermal Current (I_{th})	25 A
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V DC) 0.8 kA
Rated Short-time Withstand Current (I_{cw})	(1000 V DC) 0.8 kA for 1 s 0.8 kA
Power Loss	at Rated Operating Conditions per Pole 0.15 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism on Top of the Switch
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Door mounting
Number of Circuits	2
Number of Poles	4
Cable Cross-Section	2.5 ... 16 mm ²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	1.2...1.4 N·m
Utilization	Photovoltaic

Utilization Category

Switching of resistive loads, including moderate overloads - occasional
actuation (DC-21B)

Environmental

RoHS Status

Following EU Directive 2011/65/EU

Environmental Information

NA

Certificates and Declarations (Document Number)

CCC Certificate

CQC2012010302579872

Declaration of Conformity
- CE

1SCC301192D2704

DNV GL Certificate

1SCC301231D0201

Environmental Information

NA

Instructions and Manuals

1SCC301079M0206

RoHS Information

1SCC301192D2704

Container Information

Package Level 1 Units

box 1 piece

Package Level 1 Width

90 mm

3.5 in

Package Level 1 Depth /
Length

54 mm

2.1 in

Package Level 1 Height

90 mm

3.5 in

Package Level 1 Gross
Weight

0.3 kg

0.6 lb

Package Level 1 EAN

6417019545608

Classifications

Object Classification Code

Q

ETIM 5

EC000216 - Switch disconnecter

ETIM 6

EC000216 - Switch disconnecter

ETIM 7

EC000216 - Switch disconnecter

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

E-Number (Finland)

3601470

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

