

PRODUCT-DETAILS

OTR45B3U

OTR45B3U Enclosed Switch Disconnecter



General Information

Extended Product Type	OTR45B3U
Product ID	1SCA127687R1001
EAN	6417019576046
Catalog Description	OTR45B3U Enclosed Switch Disconnecter
Long Description	The enclosure of the OTR series is made of rigid stainless steel, class AISI304. The enclosure has a hinged door, with door lock. The cover is interlocked, and can not be opened when switch is on. The interlock function can be defeated for thermographing. Suitable for outdoor and indoor use. The end plates are blank, and can be drilled by the installer. N- and PE terminal included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340006M0013

Dimensions

Product Net Width	200 mm
Product Net Height	300 mm
Product Net Depth / Length	135 mm
Product Net Weight	3.1 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 45 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 22 kW (500 V) 22 kW (690 V) 15 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 63 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 1.4 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 1 kA
Power Loss	at Rated Operating Conditions per Pole 1.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Screw Clamp 1.5...35 mm ² Screw Clamp / PE Terminal 2pcs, 10...70 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	Blank / Blank
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Stainless steel
Maximum Mounted Auxiliary Contacts	1 NO, 2 NC
Mounted Auxiliary Contacts	0 NO, 0 NC

Environmental

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC340006D2704
Instructions and Manuals	1SCC340006M0013
RoHS Information	1SCC340034D0203

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	212 mm
Package Level 1 Depth / Length	313 mm
Package Level 1 Height	191 mm
Package Level 1 Gross Weight	3.3 kg
Package Level 1 EAN	6417019576046

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

