

PRODUCT-DETAILS

OTU45BA4MS3

OTU45BA4MS3 Enclosed Switch Disconnecter



General Information

Extended Product Type	OTU45BA4MS3
Product ID	1SCA132691R1001
EAN	6417019617961
Catalog Description	OTU45BA4MS3 Enclosed Switch Disconnecter
Long Description	The enclosure in the OTU series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are of knock out type, for 2 parallel cables, both from top and bottom. The handle is padlockable and made for three padlocks. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal.

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340156M0205
Mechanical Drawings	SONT201413R40.stp

Dimensions

Product Net Width	146 mm
Product Net Height	200 mm
Product Net Depth / Length	104 mm
Product Net Weight	0.73 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 45 A (690 V) 45 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 45 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 22 kW (500 V) 22 kW (690 V) 15 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 63 A
Rated Impulse Withstand Voltage (U_{imp})	1.5 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 1.4 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 1 kA
Rated Conditional Short- Circuit Current (I_{nc})	13 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 1.5 W
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Round handle
Standards	IEC 60947-1, -3
Number of Poles	4
Connecting Capacity Main Circuit	Screw Clamp 1.5...35 mm ² Screw Clamp / PE Terminal 2pcs, 2.5...16 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xø40.5 / 2xø40.5
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Type	Son
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Tightening Torque	2 N·m
Mechanical Durability	20000 cycle

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

BV Certificate	1SCC340018D0204
Declaration of Conformity - CE	1SCC340003D2704
Instructions and Manuals	1SCC340156M0205

Container Information

Package Level 1 Units	two pack 1 piece
Package Level 1 Width	215 mm
Package Level 1 Depth / Length	315 mm
Package Level 1 Height	150 mm
Package Level 1 Gross Weight	0.81 kg
Package Level 1 EAN	6417019617961

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

