

PRODUCT-DETAILS

OTM630E3YM230C

OTM630E3YM230C MOTORIZED BYPASS SWITCH



General Information	
Extended Product Type	OTM630E3YM230C
Product ID	1SCA136615R1001
EAN	6417019651453
Catalog Description	OTM630E3YM230C MOTORIZED BYPASS SWITCH
Long Description	OTM630E3YM230C MOTORIZED BYPASS SWITCH, Direct mounted handle, Open transition

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

Dimensions	
Product Net Width	415 mm

Product Net Height	250 mm
Product Net Depth / Length	450 mm
Product Net Weight	35 kg

Technical	_
Rated Operational Current AC-21A (I _e)	(380 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A (I _e)	(380 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-23A (I _e)	(380 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Power AC-23A (P _e)	(380 415 V) 355 kW (500 V) 400 kW (690 V) 630 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 630 A
Motor Operational Voltage	220 240 V AC
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Transition Type	Open

Certificates and Declarations (Document Number)

Instructions and 1SCC301080M0003 Manuals

Container Information

Package Level 1 Units	1 piece
Package Level 1 Gross Weight	55 kg
Package Level 1 EAN	6417019651453

Classifications

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

OTM630E3YM230C 3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ by pass\ switches$

