

PRODUCT-DETAILS

OS63GD000LAA3BZ

OS63GD000LAA3BZ Enclosed switch fuse



General Information

Extended Product Type	OS63GD000LAA3BZ
Product ID	1SCA136801R1001
EAN	6417019652696
Catalog Description	OS63GD000LAA3BZ Enclosed switch fuse

Long Description

The enclosed switch fuse disconnecter is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallel cables. Cable entry types can be blank , ring-flange or C-flange type (FL21). Cable entry plates needs to be added. There are different cable configurations, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermographing.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical

1SCC340015C0201

Information

Instructions and Manuals

1SCC340004M0004

Dimensions

Product Net Width	250 mm
Product Net Height	400 mm
Product Net Depth / Length	180 mm
Product Net Weight	7.81 kg 17.22 lb

Technical

Rated Operational Current AC-22A (I_g)	(380 ... 415 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_g)	(380 ... 415 V) 63 A (690 V) 63 A
Conventional Thermal Current (I_{the})	Fully Enclosed 63 A
Rated Impulse Withstand Voltage (U_{imp})	2.5 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	690 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 2.5 kA
Rated Conditional Short- Circuit Current (I_{nc})	13.5 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Fuse System	DIN
Standards	IEC 60947-3
Number of Poles	3
Connecting Capacity Main Circuit	Screw Clamp 2.5...25 mm ² Screw Clamp / PE Terminal 2pcs, 10...70 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	Open / Open
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Type	MSC
Enclosure Material	Steel sheet
Maximum Mounted Auxiliary Contacts	2 NO, 1 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Tightening Torque	3.5 N·m
Mechanical Durability	20000 cycle
Fuse Type	DIN 000

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC340009D2703
Instructions and Manuals	1SCC340004M0004
RoHS Information	1SCC311107D0202

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	295 mm
Package Level 1 Depth / Length	510 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	9 kg 19.84 lb
Package Level 1 EAN	6417019652696

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch Fuses

