


PRODUCT-DETAILS

OT160EVAUR6TZ

OT160EVAUR6TZ Safety switch



General Information

Extended Product Type	OT160EVAUR6TZ
Product ID	1SCA147988R1001
EAN	6417019773131
Catalog Description	OT160EVAUR6TZ Safety switch

Long Description

The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallel cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermographing.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
-----------------------------------	-----------------

Instructions and Manuals

1SCC340005M0007

Mechanical Drawings

OTKM608023PBL8RDD

Dimensions

Product Net Width	800 mm
Product Net Height	600 mm
Product Net Depth / Length	230 mm
Product Net Weight	35.6 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 80 kW (500 V) 112 kW (690 V) 144 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 160 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 30 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kA
Rated Conditional Short- Circuit Current (I_{nc})	24 kA
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Bottom In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	6
Connecting Capacity Main Circuit	Hole Diameter 8 mm Screw Clamp / PE Terminal 4pcs, 10...70 mm ²
Cable Entry Position	Down/Down
Cable Outlets Per Side	Blank / 8xring-flange, Knock-outs: 10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Type	MSC
Enclosure Material	Steel sheet
Maximum Mounted Auxiliary Contacts	4 NO, 2 NC
Mounted Auxiliary Contacts	4 NO, 2 NC
Terminal Type	Bolt

Tightening Torque

6 N·m

Environmental

RoHS Status

Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Declaration of Conformity
- CE

1SCC340002D2703

Instructions and Manuals

1SCC340005M0007

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 815 mm

Package Level 1 Depth /
Length 910 mm

Package Level 1 Height 325 mm

Package Level 1 Gross
Weight 40 kg

Package Level 1 EAN 6417019773131

Classifications

Object Classification Code

Q

ETIM 5 EC000216 - Switch disconnecter

ETIM 6 EC000216 - Switch disconnecter

ETIM 7 EC000216 - Switch disconnecter

WEEE Category 4. Large Equipment (Any External Dimension More Than 50 cm)

E-Number (Finland) 3640422

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

