

PRODUCT-DETAILS

OT125GFCC3T

OT125GFCC3T Safety switch



General Information

Extended Product Type	OT125GFCC3T
Product ID	1SCA148608R1001
EAN	6417019781389
Catalog Description	OT125GFCC3T Safety switch
Long Description	The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. PE terminals included.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340015M0004

Dimensions

Product Net Width	280 mm
Product Net Height	380 mm
Product Net Depth / Length	130 mm
Product Net Weight	3.4 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 55 kW (500 V) 75 kW (690 V) 110 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 125 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 12 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 4 kA
Rated Conditional Short- Circuit Current (I_{nc})	24 kA
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Screw Clamp 10...70 mm ² Screw Clamp / PE Terminal 2pcs, 10...70 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	II-flange / II-flange
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Type	Fibox
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	1 NO, 1 NC
Terminal Type	Screw Terminals
Tightening Torque	6 N·m

Environmental

RoHS Status

Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Declaration of Conformity
- CE1SCC340002D2703

Instructions and Manuals

1SCC340015M0004

Container Information

Package Level 1 Units	box 1 piece
-----------------------	-------------

Package Level 1 Width	295 mm
-----------------------	--------

Package Level 1 Depth / Length	510 mm
-----------------------------------	--------

Package Level 1 Height	265 mm
------------------------	--------

Package Level 1 Gross Weight	4.5 kg
---------------------------------	--------

Package Level 1 EAN	6417019781389
---------------------	---------------

Classifications

Object Classification Code	Q
----------------------------	---

ETIM 5	EC000216 - Switch disconnecter
--------	--------------------------------

ETIM 6	EC000216 - Switch disconnecter
--------	--------------------------------

ETIM 7	EC000216 - Switch disconnecter
--------	--------------------------------

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

E-Number (Finland)	3640405
--------------------	---------

E-Number (Sweden)	3134565
-------------------	---------

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

