

## PRODUCT-DETAILS

# OXB800E3X3QB

## OXB800E3X3QB AUTOMATIC TRANSFER SWITCH



### General Information

|                       |                                        |
|-----------------------|----------------------------------------|
| Extended Product Type | OXB800E3X3QB                           |
| Product ID            | 1SCA150942R1001                        |
| EAN                   | 6417019811789                          |
| Catalog Description   | OXB800E3X3QB AUTOMATIC TRANSFER SWITCH |

|                  |                                                                                                                                                                                           |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | The all-new TruONE is the world's first true purpose-built automatic transfer switch, engineered to incorporate switch and controller in one seamless unit.                               |
|                  | Performance tested beyond standard requirements, TruONE stands ready to ensure the steady delivery of critical power at all times.                                                        |
|                  | Its self-contained design reduces the number of wires and connections, which speeds installation and minimizes the potential for connection failures to ensure best-in-class reliability. |
|                  | Its predictive maintenance and modular components reduce downtime and service costs. And its advanced connectivity is ready for the future.                                               |
|                  | Every TruONE features a wide voltage range from 200 to 480 VAC (with +/-20% tolerance), reducing the need to stock multiple SKUs, reducing inventory and saving space in the warehouse.   |
|                  | Main characteristics of this particular TruONE type:<br>Open style ATS, delayed transition type I-O-II operation, Level 3 controller (LCD)                                                |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

## Popular Downloads

|                                   |                                                                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Data Sheet, Technical Information | 1SCC303008C0201                                                                                                                          |
| Instructions and Manuals          | 1SCC303011M0201                                                                                                                          |
| Mechanical Drawings               | OX_500-800E_3X3_B_.stp<br>1SCC308257F0001<br>1SCC308256F0001<br>1SCC308177F0001<br>1SCC308176F0001<br>1SCC308331F0001<br>1SCC308330F0001 |
| Wiring Diagram                    | Circuit diagram_OXB_B_.dxf<br>Circuit diagram_OXB_B_.pdf                                                                                 |

## Dimensions

|                            |                      |
|----------------------------|----------------------|
| Product Net Width          | 447 mm<br>17.6 in    |
| Product Net Height         | 313 mm<br>12.32 in   |
| Product Net Depth / Length | 212 mm<br>8.35 in    |
| Product Net Weight         | 19.12 kg<br>42.15 lb |

## Technical

|                                                    |                                  |
|----------------------------------------------------|----------------------------------|
| Rated Operational Current AC-31B ( $I_e$ )         | (200 ... 415 V AC) 800 A         |
| Rated Operational Current AC-32B ( $I_e$ )         | (200 ... 415 V AC) 800 A         |
| Rated Operational Current AC-33B ( $I_e$ )         | (200 ... 415 V AC) 800 A         |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | $q = 40\text{ °C}$ 800 A         |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 12 kV                            |
| Rated Insulation Voltage ( $U_i$ )                 | 1000 V                           |
| Rated Operational Voltage                          | Main Circuit 200 ... 480 V AC    |
| Rated Frequency (f)                                | Main Circuit 50-60 Hz            |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | for 0.1 s 42 kiloampere rms      |
| Pollution Degree                                   | 3                                |
| Handle Type                                        | Direct mounted handle            |
| Position of Line Terminals                         | Supplies on Bottom - Load on Top |
| Standards                                          | IEC60947-6-1                     |
| Controller Type                                    | Level 3 (LCD)                    |
| Special Functions                                  | Open style                       |
| Number of Poles                                    | 3                                |
| Degree of Protection                               | Front IP20                       |

|                 |         |
|-----------------|---------|
| Terminal Type   | Bolt    |
| Transition Type | Delayed |

Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC303062D2701 |
| Instructions and Manuals          | 1SCC303011M0201 |

Container Information

|                                   |                      |
|-----------------------------------|----------------------|
| Package Level 1 Units             | box 1 piece          |
| Package Level 1 Width             | 345 mm<br>13.58 in   |
| Package Level 1 Depth /<br>Length | 565 mm<br>22.24 in   |
| Package Level 1 Height            | 240 mm<br>9.45 in    |
| Package Level 1 Gross<br>Weight   | 19.92 kg<br>43.92 lb |
| Package Level 1 EAN               | 6417019811789        |

Classifications

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 6        | EC000216 - Switch disconnecter                             |
| ETIM 7        | EC000216 - Switch disconnecter                             |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Automatic Transfer Switches TruONE

