

PRODUCT-DETAILS

OTDC600UFS22

OTDC600UFS22 PV Disconnect Switch



General Information

Extended Product Type	OTDC600UFS22
Product ID	1SCA158364R1001
EAN	6417019874654
Catalog Description	OTDC600UFS22 PV Disconnect Switch
Long Description	A fully optimized four-pole DC switch-disconnector for 1000V utility-scale photovoltaic power plants covering 315-630A current range. The new design offers both a size reduction and an increase in efficiency and performance. The four-pole 1000V DC Switch helps manufacturers improve system efficiency. The compact size of the new OTDC range makes it possible for manufacturers to reduce the size of combiner boxes and inverters. Main characteristics for this switch: Disconnect double PV circuit, Approved according to UL98B and IEC 60947-1,-3, Factory fitted connection bar kits

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Last Ordering Date	2021-05-31 All Countries
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
-----------------------------------	-----------------

Instructions and Manuals	1SCC301099M0201 9AKK107492A6191
Mechanical Drawings	OTDC600UFSV22_stp OTDC600UFSV22_igs 1SCC307682F0001 1SCC307683F0001
Wiring Diagram	1SCC301032K0201

Dimensions

Product Frame Size	M
Product Net Width	278 mm 10.9 in
Product Net Height	335.5 mm 13.2 in
Product Net Depth / Length	135 mm 5.3 in
Product Net Weight	9.2 kg 20.2 lb

Technical

Connection Configuration	Double circuit 3
Rated Operational Current DC-21B (I_e)	(1000 V) 630 A
Rated Operational Current DC-22B	(1000 V) 400 A
Rated Operational Current DC-PV1	(1000 V) 500 A
Rated Operational Current DC-PV2	(1000 V) 500 A
Conventional Free-air Thermal Current (I_{th})	630 A
Conventional Thermal Current (I_{the})	Fully Enclosed 630 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1500 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V DC) 10 kA
Rated Short-time Withstand Current (I_{cw})	(1500 V DC) 10 kA for 1 s 10 kA
Protection Type	Circuit breaker
Power Loss	at Rated Operating Conditions per Pole 32 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Shaft Diameter	12 mm 0.47 in
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Position of Line Terminals	Bottom In - Bottom Out
Operating Mode	Front Operated
Standards	UL98B and IEC 60947-1, -3
Special Functions	US single-wire break
Mounting Type	Base mounting
Number of Circuits	2
Number of Poles	4

Degree of Protection	Front IP20
Terminal Type	Lug terminals
Terminal Width	30 mm 1.2 in
Tightening Torque	Cable Lug 30...40 N·m
Mechanical Durability	10000 cycle
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B) Switching of mixed resistive and inductive loads, including moderate overloads (i.e. shunt motors) - occasional actuation (DC-22B) Switching of single PV string(s) without reverse and overcurrents (DC-PV1) Switching of several PV string(s) with reverse and overcurrents (DC-PV2)

Technical UL/CSA

Maximum Operating Voltage UL/CSA	1000 V DC
Ampere Rating UL/CSA	1000VDC 600 A
Tightening Torque UL/CSA	Cable Lug 30...44 N·m Cable Lug 266...390 lbf·in

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CCC Certificate	CQC2019010302206498
Declaration of Conformity - CE	1SCC301227D2701
DNV GL Certificate	1SCC301231D0201
Instructions and Manuals	1SCC301099M0201 9AKK107492A6191
RoHS Information	1SCC301227D2701
UL Certificate	UL certificate OTDC250-1000UF

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	310 mm 12.2 in
Package Level 1 Depth / Length	410 mm 16.1 in
Package Level 1 Height	200 mm 7.9 in
Package Level 1 Gross Weight	9.7 kg 21.4 lb
Package Level 1 EAN	6417019874654

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter

UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

