

PRODUCT-DETAILS

T6L800 TMD800-2000 3p FF 1000Vac+ACC xGE

T6L800 TMD800-2000 3p FF 1000Vac+ACC xGE

General Information

Extended Product Type	T6L800 TMD800-2000 3p FF 1000Vac+ACC xGE
Product ID	1SDA066042R1
EAN	8015644690410
Catalog Description	T6L800 TMD800-2000 3p FF 1000Vac+ACC xGE
Long Description	C.BREAKER TMAX T6L 800 1000V AC FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 800-2000 A WITH: KIT FC CuAl 3x185mm ² T6 800-S6 800 6pcs UVR-C T4-5-6 220...250 Vac/dc L=3m SP.VE. AUX-C T4-5-6 1Q 1SY 24 Vdc L=3m SP.VE. MOE T6 220.

Ordering

EAN	8015644690410
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	9.5 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Gross Weight	11 kg

Additional Information

Number of Poles	3
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Operational Voltage	690 V AC 750 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(230 V AC) 200 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u)	800 A
Short-Circuit Performance Level	L
Standards	IEC
Sub-type	T6
Version	F

Certificates and Declarations (Document Number)

Instructions and Manuals	1SDC210033D0202
--------------------------	-----------------

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

