

## PRODUCT-DETAILS

# XT4H 160 TMD 20-300 3p F F

## XT4H 160 TMD 20-300 3p F F



### General Information

|                       |                                                                                                         |
|-----------------------|---------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT4H 160 TMD 20-300 3p F F                                                                              |
| Product ID            | 1SDA068333R1                                                                                            |
| EAN                   | 8015644696399                                                                                           |
| Catalog Description   | XT4H 160 TMD 20-300 3p F F                                                                              |
| Long Description      | C.BREAKER TMAX XT4H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 20-300 A |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644696399 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 105 mm  |
| Product Net Height         | 160 mm  |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight         | 2.05 kg |

### Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 145 mm        |
| Package Level 1 Height         | 210 mm        |
| Package Level 1 Depth / Length | 168 mm        |
| Package Level 1 Gross Weight   | 2.5 kg        |
| Package Level 1 EAN            | 8015644696399 |

## Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Additional Information

|                                                             |                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Power Distribution                                                                                                                                                                                                                                                                                    |
| Current Type                                                | AC/DC                                                                                                                                                                                                                                                                                                 |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle                                                                                                                                                                                                                                                                     |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle                                                                                                                                                                                                                                      |
| Number of Poles                                             | 3                                                                                                                                                                                                                                                                                                     |
| Opening Time                                                | CB with SOR 15 ms<br>CB with UVR 15 ms                                                                                                                                                                                                                                                                |
| Order Multiple                                              | 1 piece                                                                                                                                                                                                                                                                                               |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                                                                                                                                          |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                                                                                                                                          |
| Product Type                                                | CB                                                                                                                                                                                                                                                                                                    |
| Rated Current ( $I_n$ )                                     | 20 A                                                                                                                                                                                                                                                                                                  |
| Rated Frequency (f)                                         | 50 / 60 Hz                                                                                                                                                                                                                                                                                            |
| Rated Voltage ( $U_r$ )                                     | 690 V                                                                                                                                                                                                                                                                                                 |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                                                                                                                                  |
| Rated Instantaneous Short-Circuit Current Setting ( $I_i$ ) | 300 A                                                                                                                                                                                                                                                                                                 |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                                                                                                                                                                |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC                                                                                                                                                                                                                                                                                  |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 45 kA<br>(690 V AC) 15 kA<br>(250 V DC) 2 Poles in Series 70 kA<br>(500 V DC) 2 Poles in Series 70 kA<br>(500 V DC) 3 Poles in Series 70 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 45 kA<br>(690 V AC) 15 kA                                                                                                                   |

|                                               |                                                                                                                |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------|
|                                               | (250 V DC) 2 Poles in Series 70 kA<br>(500 V DC) 2 Poles in Series 70 kA<br>(500 V DC) 3 Poles in Series 70 kA |
| Rated Uninterrupted Current (I <sub>u</sub> ) | 160 A                                                                                                          |
| Release                                       | TMD                                                                                                            |
| Release Type                                  | TM                                                                                                             |
| Setting Range                                 | 14...20 A                                                                                                      |
| Short-Circuit Performance Level               | H                                                                                                              |
| Standards                                     | IEC                                                                                                            |
| Sub-type                                      | XT4                                                                                                            |
| Terminal Connection Type                      | Fixed Circuit-Breakers                                                                                         |
| Version                                       | F                                                                                                              |

### Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK106713A5529                    |
| Environmental Information         | 1SDL000190R0001                    |
| GL Certificate                    | 1SDL000163R0095                    |
| Instructions and Manuals          | 1SDH000722R0001                    |
| LR Certificate                    | 1SDL000163R0100                    |

### Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| UNSPSC                     | 39120000                                                                     |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

### Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

