

## PRODUCT-DETAILS

XT4S 250 MA 200 Im=1000...2000 3p F F

XT4S 250 MA 200 Im=1000...2000 3p F F



### General Information

|                       |                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT4S 250 MA 200 Im=1000...2000 3p F F                                                                              |
| Product ID            | 1SDA068440R1                                                                                                       |
| EAN                   | 8015644023461                                                                                                      |
| Catalog Description   | XT4S 250 MA 200 Im=1000...2000 3p F F                                                                              |
| Long Description      | C.BREAKER TMAX XT4S 250 FIXED THREE-POLE WITH FRONT TERMINALS AND<br>MAGNETIC RELEASE MA lu 200 A I3=1000...2000 A |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644023461 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensions

|                               |         |
|-------------------------------|---------|
| Product Net Width             | 105 mm  |
| Product Net Height            | 160 mm  |
| Product Net Depth /<br>Length | 82.5 mm |
| Product Net Weight            | 2.05 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 145 mm        |
| Package Level 1 Height         | 210 mm        |
| Package Level 1 Depth / Length | 168 mm        |
| Package Level 1 Gross Weight   | 2.5 kg        |
| Package Level 1 EAN            | 8015644023461 |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Additional Information

|                                                             |                                                                                                                                                              |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Motor Protection                                                                                                                                             |
| Current Type                                                | AC/DC                                                                                                                                                        |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle                                                                                                                            |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle                                                                                             |
| Number of Poles                                             | 3                                                                                                                                                            |
| Opening Time                                                | CB with SOR 15 ms<br>CB with UVR 15 ms                                                                                                                       |
| Order Multiple                                              | 1 piece                                                                                                                                                      |
| Power Loss                                                  | at Rated Operating Conditions per Pole 11.88 W                                                                                                               |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                 |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                 |
| Product Type                                                | CB                                                                                                                                                           |
| Rated Current ( $I_n$ )                                     | 200 A                                                                                                                                                        |
| Rated Frequency (f)                                         | 50 / 60 Hz                                                                                                                                                   |
| Rated Voltage ( $U_r$ )                                     | 690 V                                                                                                                                                        |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                         |
| Rated Instantaneous Short-Circuit Current Setting ( $I_s$ ) | 1000...2000 A                                                                                                                                                |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                       |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC                                                                                                                                         |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(240 V AC) 85 kA<br>(380 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 36 kA<br>(525 V AC) 25 kA |

|                                                                |                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                | (690 V AC) 12 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 3 Poles in Series 50 kA                                                                                                                                                                 |
| Rated Ultimate Short-Circuit Breaking Capacity<br>( $I_{cu}$ ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(240 V AC) 85 kA<br>(380 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 36 kA<br>(525 V AC) 25 kA<br>(690 V AC) 12 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 3 Poles in Series 50 kA |
| Rated Uninterrupted Current ( $I_u$ )                          | 250 A                                                                                                                                                                                                                                                                                              |
| Release                                                        | MA                                                                                                                                                                                                                                                                                                 |
| Release Type                                                   | M                                                                                                                                                                                                                                                                                                  |
| Short-Circuit Performance Level                                | S                                                                                                                                                                                                                                                                                                  |
| Standards                                                      | IEC                                                                                                                                                                                                                                                                                                |
| Sub-type                                                       | XT4                                                                                                                                                                                                                                                                                                |
| Terminal Connection Type                                       | Fixed Circuit-Breakers                                                                                                                                                                                                                                                                             |
| Version                                                        | F                                                                                                                                                                                                                                                                                                  |

## Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK106713A5529                    |
| Environmental Information         | 1SDL000190R0001                    |
| GL Certificate                    | 1SDL000163R0095                    |
| Instructions and Manuals          | 1SDH000722R0001                    |
| LR Certificate                    | 1SDL000163R0100                    |
| RoHS Information                  | LB-DT 17-21D                       |

## Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| UNSPSC                     | 39120000                                                                     |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

