

PRODUCT-DETAILS

E2.2S 2000 Ekip Dip LSIG 3p F HR

E2.2S 2000 Ekip Dip LSIG 3p F HR



General Information

Extended Product Type	E2.2S 2000 Ekip Dip LSIG 3p F HR
Product ID	1SDA071043R1
EAN	8015644748937
Catalog Description	E2.2S 2000 Ekip Dip LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2S 2000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN	8015644748937
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	46 kg
Package Level 1 EAN	8015644748937

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 10000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	212 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs})	100 %
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC

Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
Environmental Information	Not Available
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

