

PRODUCT-DETAILS

E1.2B 800 Ekip Dip LSIG 4p WMP

E1.2B 800 Ekip Dip LSIG 4p WMP



General Information

Extended Product Type	E1.2B 800 Ekip Dip LSIG 4p WMP
Product ID	1SDA072723R1
EAN	8015644765736
Catalog Description	E1.2B 800 Ekip Dip LSIG 4p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2B 800 FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN	8015644765736
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	348 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	20 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	350 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	23 kg
Package Level 1 EAN	8015644765736

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Current Type	AC
Electrical Durability	Ue = < 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Neutral Pole Current ([% I _n])	100 %
Number of Poles	4
Power Loss	100 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cs}	100 %
Rated Current (I _n)	800 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 42 kA (230 V AC) 42 kA (380 V AC) 42 kA (400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 42 kA for 3 s 24 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA (500 V AC) 42 kA (525 V AC) 42 kA (690 V AC) 42 kA
Rated Uninterrupted Current (I _u)	800 A
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit	B

Performance Level	
Standards	IEC
Sub-type	E1.2
Version	W

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
Environmental Information	Not Available
Instructions and Manuals	1SDH000999R0002

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

