

PRODUCT-DETAILS

E2.2H 800 Ekip Dip LSI 4p WMP

E2.2H 800 Ekip Dip LSI 4p WMP



General Information

Extended Product Type	E2.2H 800 Ekip Dip LSI 4p WMP
Product ID	1SDA072892R1
EAN	8015644767426
Catalog Description	E2.2H 800 Ekip Dip LSI 4p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2H 800 FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LSI R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN	8015644767426
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	407 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	55 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	60 kg
Package Level 1 EAN	8015644767426

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Neutral Pole Current ([% I _n])	100 %
Number of Poles	4
Power Loss	72 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cs}	100 %
Rated Current (I _n)	800 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 85 kA (660 V AC) 85 kA (690 V AC) 85 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 85 kA for 3 s 66 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 85 kA (525 V AC) 85 kA (690 V AC) 85 kA
Rated Uninterrupted Current (I _u)	800 A
Release	Ekip Dip LSI
Release Type	EL
Short-Circuit	H

Performance Level	
Standards	IEC
Sub-type	E2.2
Version	W

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
Environmental Information	Not Available
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

