

## PRODUCT-DETAILS

# XT1S 160 TMF 16-450 3p F F

## XT1S 160 TMF 16-450 3p F F



### General Information

|                       |                                                                                                         |
|-----------------------|---------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT1S 160 TMF 16-450 3p F F                                                                              |
| Product ID            | 1SDA080830R1                                                                                            |
| EAN                   | 8015644873486                                                                                           |
| Catalog Description   | XT1S 160 TMF 16-450 3p F F                                                                              |
| Long Description      | C.BREAKER TMAX XT1S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 16-450 A |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644873486 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 76.2 mm |
| Product Net Height         | 130 mm  |
| Product Net Depth / Length | 70 mm   |
| Product Net Weight         | 1 kg    |

### Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 128 mm        |
| Package Level 1 Height         | 135 mm        |
| Package Level 1 Depth / Length | 143 mm        |
| Package Level 1 Gross Weight   | 1.1 kg        |
| Package Level 1 EAN            | 8015644873486 |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Additional Information

|                                                             |                                                                                                                                                                                                                                                                          |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Power Distribution                                                                                                                                                                                                                                                       |
| Current Type                                                | AC/DC                                                                                                                                                                                                                                                                    |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle                                                                                                                                                                                                                                        |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle                                                                                                                                                                                                         |
| Number of Poles                                             | 3                                                                                                                                                                                                                                                                        |
| Opening Time                                                | CB with SOR 15 ms<br>CB with UVR 15 ms                                                                                                                                                                                                                                   |
| Order Multiple                                              | 1 piece                                                                                                                                                                                                                                                                  |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                                                                                                             |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                                                                                                             |
| Product Type                                                | CB                                                                                                                                                                                                                                                                       |
| Rated Current ( $I_n$ )                                     | 16 A                                                                                                                                                                                                                                                                     |
| Rated Voltage ( $U_r$ )                                     | 690 V                                                                                                                                                                                                                                                                    |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                                                                                                     |
| Rated Instantaneous Short-Circuit Current Setting ( $I_i$ ) | 450 A                                                                                                                                                                                                                                                                    |
| Rated Insulation Voltage ( $U_i$ )                          | 800 V                                                                                                                                                                                                                                                                    |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC                                                                                                                                                                                                                                                     |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 63.75 kA<br>(230 V AC) 63.75 kA<br>(240 V AC) 63.75 kA<br>(380 V AC) 50 kA<br>(415 V AC) 37.5 kA<br>(440 V AC) 25 kA<br>(500 V AC) 18 kA<br>(525 V AC) 17.5 kA<br>(690 V AC) 5 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 3 Poles in Series 50 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(240 V AC) 85 kA<br>(380 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 36 kA<br>(525 V AC) 35 kA<br>(690 V AC) 8 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 3 Poles in Series 50 kA              |

|                                               |                        |
|-----------------------------------------------|------------------------|
| Rated Uninterrupted Current (I <sub>u</sub> ) | 160 A                  |
| Release                                       | TMF                    |
| Release Type                                  | TM                     |
| Setting Range                                 | 16 A                   |
| Short-Circuit Performance Level               | S                      |
| Standards                                     | IEC                    |
| Sub-type                                      | XT1                    |
| Terminal Connection Type                      | Fixed Circuit-Breakers |
| Version                                       | F                      |

Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK106713A5532                    |
| Environmental Information         | 1SDL000190R0001                    |
| Instructions and Manuals          | 1SDH000719R0001                    |
| RoHS Information                  | LB-DT 17-21D                       |

Classifications

|               |                                                                              |
|---------------|------------------------------------------------------------------------------|
| ETIM 6        | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7        | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

