

PRODUCT-DETAILS

XT5N 630 MA 500-6500 3p F F

XT5N 630 MA 500-6500 3p F F



General Information

Extended Product Type	XT5N 630 MA 500-6500 3p F F
Product ID	1SDA100366R1
EAN	8056221004435
Catalog Description	XT5N 630 MA 500-6500 3p F F
Long Description	C.BREAKER TMAX XT5N 630 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE MA R 500 I3=3500...6500

Ordering

EAN	8056221004435
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.775 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	250 mm
Package Level 1 Height	245 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.263 kg
Package Level 1 EAN	8056221004435

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Circuit Breaker Type to be Associated	Motor Protection
Current Type	AC/DC
Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	33.5 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	500 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I_s)	3500...6500 A
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 6.25 kA (500 V DC) 2 Poles in Series 6.25 kA
Rated Short-time Withstand Current (I_{cw})	6 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 2 Poles in Series 25 kA
Rated Uninterrupted Current (I_u)	630 A
Release	MA
Release Type	M
Short-Circuit Performance Level	N
Standards	IEC 60947
Sub-type	XT5
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

