


PRODUCT-DETAILS

XT5S 630 TMA 500-5000 4p F F InN=100%In

XT5S 630 TMA 500-5000 4p F F InN=100%In



General Information

Extended Product Type	XT5S 630 TMA 500-5000 4p F F InN=100%In
Product ID	1SDA100457R1
EAN	8056221005340
Catalog Description	XT5S 630 TMA 500-5000 4p F F InN=100%In
Long Description	C.BREAKER TMAX XT5S 630 FIXED WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE FOUR-POLE IN AC-DC TMA R 500 I3=2500...5000 A FULLY RATED NEUTRAL

Ordering

EAN	8056221005340
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	250 mm
Package Level 1 Height	245 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221005340

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC/DC
Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Power Loss	33.5 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	500 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I_s)	2500...5000 A
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 30 kA (525 V AC) 30 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 7.5 kA (500 V DC) 2 Poles in Series 7.5 kA
Rated Short-time	6 kA

Withstand Current (I_{cw})

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA
	(230 V AC) 85 kA
	(240 V AC) 85 kA
	(380 V AC) 50 kA
	(415 V AC) 50 kA
	(440 V AC) 50 kA
	(500 V AC) 30 kA
	(525 V AC) 30 kA
	(690 V AC) 25 kA
	(250 V DC) 2 Poles in Series 30 kA
	(500 V DC) 2 Poles in Series 30 kA
Rated Uninterrupted Current (I_u)	630 A
Release	TMA
Release Type	TM
Setting Range	350...500 A
Short-Circuit Performance Level	S
Standards	IEC 60947
Sub-type	XT5
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210100D0205
	1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

