

## PRODUCT-DETAILS

# XT5H 400 Ekip Dip LSIG In=250 3p F F

# XT5H 400 Ekip Dip LSIG In=250 3p F F



## General Information

|                       |                                                                                                                 |
|-----------------------|-----------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT5H 400 Ekip Dip LSIG In=250 3p F F                                                                            |
| Product ID            | 1SDA100496R1                                                                                                    |
| EAN                   | 8056221005739                                                                                                   |
| Catalog Description   | XT5H 400 Ekip Dip LSIG In=250 3p F F                                                                            |
| Long Description      | C.BREAKER TMAX XT5H 400 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 250 |

## Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8056221005739 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 140 mm   |
| Product Net Height         | 205 mm   |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight         | 4.82 kg  |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 250 mm        |
| Package Level 1 Height         | 245 mm        |
| Package Level 1 Depth / Length | 285 mm        |
| Package Level 1 Gross Weight   | 5.308 kg      |
| Package Level 1 EAN            | 8056221005739 |

## Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Additional Information

|                                                             |                                                                                                                                                                                     |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Power Distribution                                                                                                                                                                  |
| Current Type                                                | AC                                                                                                                                                                                  |
| Electrical Durability                                       | 120 cycles per hour<br>7000 cycle                                                                                                                                                   |
| Mechanical Durability                                       | 240 cycles per hour<br>20000 cycle                                                                                                                                                  |
| Number of Poles                                             | 3                                                                                                                                                                                   |
| Order Multiple                                              | 1 piece                                                                                                                                                                             |
| Power Loss                                                  | 8 W                                                                                                                                                                                 |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                        |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                        |
| Product Type                                                | CB                                                                                                                                                                                  |
| Rated Current ( $I_n$ )                                     | 250 A                                                                                                                                                                               |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                                              |
| Rated Operational Voltage                                   | 690 V AC                                                                                                                                                                            |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 50 kA<br>(690 V AC) 40 kA |
| Rated Short-time Withstand Current ( $I_{cw}$ )             | 6 kA                                                                                                                                                                                |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 50 kA<br>(690 V AC) 40 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 400 A                                                                                                                                                                               |
| Release                                                     | Ekip Dip LSIG                                                                                                                                                                       |
| Release Type                                                | EL                                                                                                                                                                                  |
| Short-Circuit Performance Level                             | H                                                                                                                                                                                   |

|                          |                        |
|--------------------------|------------------------|
| Standards                | IEC 60947              |
| Sub-type                 | XT5                    |
| Terminal Connection Type | Fixed Circuit-Breakers |
| Version                  | F                      |

Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK107680A2824                    |
| Instructions and Manuals          | 1SDH002011A1001                    |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

