


PRODUCT-DETAILS

XT5D 630 4p F F

XT5D 630 4p F F



General Information

Extended Product Type	XT5D 630 4p F F
Product ID	1SDA100549R1
EAN	8056221006255
Catalog Description	XT5D 630 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 630 FIXED FOUR-POLE WITH FRONT TERMINALS

Ordering

EAN	8056221006255
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221006255

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	SD
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current AC-23A (I _e)	(400 V) 630 A (690 V) 630 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current (I _{cw})	7.6 kA
Rated Uninterrupted Current (I _u)	630 A
Standards	IEC 60947
Sub-type	XT5
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

