


## PRODUCT-DETAILS

# XT5X 630 BREAKING PART 4p F F

## XT5X 630 BREAKING PART 4p F F



### General Information

|                       |                                                                  |
|-----------------------|------------------------------------------------------------------|
| Extended Product Type | XT5X 630 BREAKING PART 4p F F                                    |
| Product ID            | 1SDA100572R1                                                     |
| EAN                   | 8056221006484                                                    |
| Catalog Description   | XT5X 630 BREAKING PART 4p F F                                    |
| Long Description      | BREAKING PART TMAX XT5X 630 FIXED FOUR-POLE WITH FRONT TERMINALS |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8056221006484 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85389099      |

### Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 186 mm   |
| Product Net Height         | 205 mm   |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight         | 4.55 kg  |

### Container Information

|                       |         |
|-----------------------|---------|
| Package Level 1 Units | 1 piece |
|-----------------------|---------|

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 305 mm        |
| Package Level 1 Height         | 285 mm        |
| Package Level 1 Depth / Length | 370 mm        |
| Package Level 1 Gross Weight   | 12.5 kg       |
| Package Level 1 EAN            | 8056221006484 |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Additional Information

|                                                             |                                                                                                                                                                                                                                                                                                               |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical Durability                                       | 120 cycles per hour<br>7000 cycle                                                                                                                                                                                                                                                                             |
| Mechanical Durability                                       | 240 cycles per hour<br>20000 cycle                                                                                                                                                                                                                                                                            |
| Number of Poles                                             | 4                                                                                                                                                                                                                                                                                                             |
| Order Multiple                                              | 1 piece                                                                                                                                                                                                                                                                                                       |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                                                                                                                                                  |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                                                                                                                                                  |
| Product Type                                                | CBBU                                                                                                                                                                                                                                                                                                          |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                                                                                                                                          |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                                                                                                                                                                        |
| Rated Operational Voltage                                   | 690 V AC<br>750 V DC                                                                                                                                                                                                                                                                                          |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 200 kA<br>(230 V AC) 200 kA<br>(240 V AC) 200 kA<br>(380 V AC) 200 kA<br>(415 V AC) 200 kA<br>(440 V AC) 200 kA<br>(500 V AC) 150 kA<br>(525 V AC) 120 kA<br>(690 V AC) 100 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 50 kA<br>(750 V DC) 3 Poles in Series 35 kA   |
| Rated Short-time Withstand Current ( $I_{cw}$ )             | 6 kA                                                                                                                                                                                                                                                                                                          |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 200 kA<br>(230 V AC) 200 kA<br>(240 V AC) 200 kA<br>(380 V AC) 200 kA<br>(415 V AC) 200 kA<br>(440 V AC) 200 kA<br>(500 V AC) 150 kA<br>(525 V AC) 120 kA<br>(690 V AC) 100 kA<br>(250 V DC) 2 Poles in Series 100 kA<br>(500 V DC) 2 Poles in Series 100 kA<br>(750 V DC) 3 Poles in Series 70 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 630 A                                                                                                                                                                                                                                                                                                         |
| Short-Circuit Performance Level                             | X                                                                                                                                                                                                                                                                                                             |
| Standards                                                   | IEC 60947                                                                                                                                                                                                                                                                                                     |
| Sub-type                                                    | XT5                                                                                                                                                                                                                                                                                                           |
| Terminal Connection Type                                    | Fixed Circuit-Breakers                                                                                                                                                                                                                                                                                        |

Version

F

Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK107680A2824                    |
| Instructions and Manuals          | 1SDH002011A1001                    |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

