


PRODUCT-DETAILS

XT6N 1000 BREAKING PART 4p F F

XT6N 1000 BREAKING PART 4p F F



General Information

Extended Product Type	XT6N 1000 BREAKING PART 4p F F
Product ID	1SDA100791R1
EAN	8056221008457
Catalog Description	XT6N 1000 BREAKING PART 4p F F
Long Description	BREAKING PART TMAX XT6N 1000 FIXED FOUR-POLE WITH FRONT TERMINALS

Ordering

EAN	8056221008457
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	10.5 kg

Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Package Level 1 Width	305 mm
Package Level 1 Height	285 mm
Package Level 1 Depth / Length	370 mm
Package Level 1 Gross Weight	12.5 kg
Package Level 1 EAN	8056221008457

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CBBU
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 18 kA (500 V DC) 2 Poles in Series 10 kA (750 V DC) 3 Poles in Series 8 kA
Rated Short-time Withstand Current (I _{cw})	10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 2 Poles in Series 20 kA
Rated Uninterrupted Current (I _u)	1000 A
Short-Circuit Performance Level	N
Standards	IEC 60947
Sub-type	XT6
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2825
Instructions and Manuals	1SDH002012A1001

Classifications	
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

