



## PRODUCT-DETAILS

# YO-C XT6 W 110..240 Vac - 110..250 Vdc

## YO-C XT6 W 110..240 Vac - 110..250 Vdc

### General Information

|                       |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| Extended Product Type | YO-C XT6 W 110..240 Vac - 110..250 Vdc                                                            |
| Product ID            | 1SDA104938R1                                                                                      |
| EAN                   | 8015644070304                                                                                     |
| Catalog Description   | YO-C XT6 W 110..240 Vac - 110..250 Vdc                                                            |
| Long Description      | SHUNT OPENING RELEASE WIRED FOR PERMANENT SERVICE 110..240V AC- 110..250V DC FOR WITHDRAWABLE XT6 |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644070304 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85389099      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 110 mm  |
| Product Net Height         | 60 mm   |
| Product Net Depth / Length | 140 mm  |
| Product Net Weight         | 0.17 kg |

### Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 110 mm        |
| Package Level 1 Height         | 60 mm         |
| Package Level 1 Depth / Length | 140 mm        |
| Package Level 1 Gross Weight   | 0.2 kg        |
| Package Level 1 EAN            | 8015644070304 |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Additional Information

|                                 |                                  |
|---------------------------------|----------------------------------|
| Configuration Type              | Loose or configurable            |
| Current Type                    | AC/DC                            |
| Order Multiple                  | 1 piece                          |
| Product Main Type               | Accessories for Tmax XT          |
| Product Name                    | Accessory                        |
| Product Type                    | ACC                              |
| Rated Voltage (U <sub>r</sub> ) | 110...240 V AC<br>110...250 V DC |
| Standards                       | IEC, UL                          |
| Suitable For                    | XT6                              |
| Suitable for Product Class      | SACE Tamx XT                     |

## Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206<br>1SDC210200D0206 |
| Instructions and Manuals          | 1SDH002011A1514                    |

## Classifications

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 6        | EC002483 - Switch spool for power circuit breaker          |
| ETIM 7        | EC002483 - Switch spool for power circuit breaker          |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax XT

