

## PRODUCT-DETAILS

# XRG400BS-185/10-4P

## XRG400BS-185/10-4P Switch disconnecter fuse



### General Information

|                       |                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------|
| Extended Product Type | XRG400BS-185/10-4P                                                                     |
| Product ID            | 1SEP204488R3700                                                                        |
| EAN                   | 3800161652097                                                                          |
| Catalog Description   | XRG400BS-185/10-4P Switch disconnecter fuse                                            |
| Long Description      | Four pole Switch Disconnecter Fuse for 185mm busbar distance and 10mm busbar thickness |

### Ordering

|                       |               |
|-----------------------|---------------|
| Customs Tariff Number | 85363000      |
| Country of Origin     | Bulgaria (BG) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SEC313002D0201 |
| Instructions and Manuals          | 9AKK107492A8857 |
| Mechanical Drawings               | 9AKK107680A0398 |

### Dimensions

|                   |        |
|-------------------|--------|
| Product Net Width | 600 mm |
|-------------------|--------|

|                            |          |
|----------------------------|----------|
| Product Net Height         | 250 mm   |
| Product Net Depth / Length | 335 mm   |
| Product Net Weight         | 17.47 kg |

## Technical

|                                               |                                                                                                                |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Rated Operational Current AC-22B ( $I_e$ )    | (500 V) 400 A                                                                                                  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ) | 8 kV                                                                                                           |
| Rated Insulation Voltage ( $U_i$ )            | 1 kV                                                                                                           |
| Rated Operational Voltage                     | 500 V AC                                                                                                       |
| Power Loss                                    | at Rated Load 100 W                                                                                            |
| Distance Between Phases                       | 185 mm                                                                                                         |
| Fuse Size                                     | B4                                                                                                             |
| Fuse System                                   | British Standard                                                                                               |
| Operating Mode                                | Manual                                                                                                         |
| Standards                                     | IEC60947-3                                                                                                     |
| Number of Poles                               | 4                                                                                                              |
| Degree of Protection                          | acc. to IEC 60529 Front IP41                                                                                   |
| Terminal Type                                 | Bolt                                                                                                           |
| Fuse Type                                     | BS                                                                                                             |
| Electronic Fuse Monitoring                    | No                                                                                                             |
| Utilization Category                          | Switching of mixed resistive and inductive loads, including moderate overloads - occasional actuation (AC-22B) |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC311166D2701 |
| Instructions and Manuals       | 9AKK107492A8857 |
| RoHS Information               | 9AKK107991A2784 |

## Container Information

|                                |             |
|--------------------------------|-------------|
| Package Level 1 Units          | box 1 piece |
| Package Level 1 Width          | 60 mm       |
| Package Level 1 Depth / Length | 340 mm      |
| Package Level 1 Height         | 275 mm      |
| Package Level 1 Gross Weight   | 18.05 kg    |

## Classifications

|        |                                     |
|--------|-------------------------------------|
| ETIM 6 | EC001040 - Fuse switch disconnecter |
|--------|-------------------------------------|

|               |                                                             |
|---------------|-------------------------------------------------------------|
| ETIM 7        | EC001040 - Fuse switch disconnecter                         |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

---

**Categories**

---

Low Voltage Products and Systems → Fusegear → Switch Disconnecter Fuse

