

PRODUCT-DETAILS

# MP1-40W-20

## MP1-40W-20 Pushbutton



### General Information

|                       |                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------|
| Extended Product Type | MP1-40W-20                                                                             |
| Product ID            | 1SFA611100R4025                                                                        |
| EAN                   | 7320500261552                                                                          |
| Catalog Description   | MP1-40W-20 Pushbutton                                                                  |
| Long Description      | Modular Pushbutton - Momentary - Flush - White - Non-illuminated - Black plastic - 2NO |

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Sweden)      | 3715062       |
| EAN                    | 7320500261552 |
| Minimum Order Quantity | 10 piece      |
| Customs Tariff Number  | 8536501999    |

### Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 0.048 m  |
| Product Net Height         | 0.03 m   |
| Product Net Depth / Length | 0.062 m  |
| Product Net Weight         | 0.045 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | bag 1 piece   |
| Package Level 1 Width          | 0.11 m        |
| Package Level 1 Height         | 0.03 m        |
| Package Level 1 Depth / Length | 0.15 m        |
| Package Level 1 Gross Weight   | 0.045 kg      |
| Package Level 1 EAN            | 7320500261552 |

## Environmental

|                         |                                                                        |
|-------------------------|------------------------------------------------------------------------|
| Ambient Air Temperature | Operation -25 ... +70 °C<br>Storage -30 ... +85 °C                     |
| RoHS Status             | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Additional Information

|                                                   |                                       |
|---------------------------------------------------|---------------------------------------|
| Actuator Type                                     | Flush                                 |
| Bezel Material                                    | Black Plastic                         |
| Block                                             | 2NO                                   |
| Color                                             | White                                 |
| Connection Type                                   | Screw Clamp                           |
| Degree of Protection                              | Front IP66<br>Terminals IP20          |
| Device                                            | Holder for blocks incl.               |
| Function                                          | Momentary                             |
| Illumination                                      | Non-illuminated                       |
| Mechanical Durability                             | 2 million                             |
| Number of Auxiliary Contacts NO                   | 2                                     |
| Product Main Type                                 | MP1                                   |
| Product Name                                      | Pushbutton                            |
| Product Range                                     | Modular                               |
| Product Type                                      | MP                                    |
| Rated Frequency (f)                               | 50 / 60 Hz                            |
| Rated Operational Current AC-15 (I <sub>e</sub> ) | (24 / 127 V) 8 A<br>(220 / 240 V) 6 A |
| Rated Operational Current DC-13 (I <sub>e</sub> ) | (24 V) 5<br>(125 V) 1.1 A             |
| Rated Operational Voltage                         | 24 ... 690 V AC/DC                    |
| RoHS Date                                         | 0635 4                                |

## Certificates and Declarations (Document Number)

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| CQC Certificate                   | CQC2005010304154103<br>CQC2008010305274953 |
| cULus Certificate                 | 9AKK107046A9925                            |
| Data Sheet, Technical Information | 1SFC151007C02__                            |
| Declaration of Conformity - CCC   | 2020980305001528<br>2020980305001106       |
| Declaration of Conformity - CE    | 2CMT2015-005452                            |
| DNV GL Certificate                | E-14107                                    |
| Environmental Information         | 1SFC151010D0201                            |

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SFC151011M0201 |
| RoHS Information         | 2CMT2015-005452 |

| Classifications            |                                                            |  |
|----------------------------|------------------------------------------------------------|--|
| ETIM 4                     | EC002024 - Accessories for control circuit devices         |  |
| ETIM 5                     | EC000221 - Front element for push button                   |  |
| ETIM 6                     | EC000221 - Front element for push button                   |  |
| ETIM 7                     | EC001028 - Push button, complete                           |  |
| Object Classification Code | S                                                          |  |
| UNSPSC                     | 39121500                                                   |  |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |  |
| eClass                     | V11.0 : 27371228                                           |  |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

