

PRODUCT-DETAILS

KPR4-100B

KPR4-100B Reset Pushbutton



General Information

Extended Product Type	KPR4-100B
Product ID	1SFA616163R1006
EAN	7320500548240
Catalog Description	KPR4-100B Reset Pushbutton
Long Description	Modular Reset Pushbutton - Momentary, with shaft - Extended - Black - Non-illuminated - Black Plastic - No text

Ordering

E-Number (Finland)	2338509
EAN	7320500548240
Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.215 m
Product Net Weight	0.019 kg

Container Information

Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.25 m
Package Level 1 Height	0.03 m
Package Level 1 Depth / Length	0.1 m
Package Level 1 Gross Weight	0.19 kg
Package Level 1 EAN	7320500249161

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Actuator Type	Extended
Bezel Material	Black Plastic
Color	Black
Degree of Protection	Front IP66
Function	Momentary
Illumination	Non-illuminated
Mechanical Durability	2 million
Product Main Type	KPR4
Product Name	Reset Pushbutton
Product Range	Modular
Product Type	KPR
RoHS Date	0626 5
Sub-Function	With shaft
Upper Button Text	RUECKSTELLTASTE KPR4-100B HOCH MIT STOESSEL SCHWARZ

Certificates and Declarations (Document Number)

cULus Certificate	9AKK107046A9924
Data Sheet, Technical Information	1SFC151007C02__
Declaration of Conformity - CE	2CMT2015-005453
Environmental Information	1SFC151001D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005453

Classifications

ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC000221 - Front element for push button
ETIM 6	EC000221 - Front element for push button
ETIM 7	EC000221 - Front element for push button
Object Classification Code	S
UNSPSC	39121500
WEEE Category	Product Not in WEEE Scope
eClass	V11.0 : 27371210

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

