

PRODUCT-DETAILS

CP1-11G-10-1071

PUSHBUTTON CP1-11G-10-1071



General Information

Extended Product Type	CP1-11G-10-1071
Product ID	1SFA619199R1071
EAN	7320500554463
Catalog Description	PUSHBUTTON CP1-11G-10-1071
Long Description	PUSHBUTTON CP1-11G-10-1071

Ordering

EAN	7320500554463
Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 mm
Product Net Depth / Length	0.055 m
Product Net Weight	0.025 kg

Container Information

Package Level 1 Units	bag 10 piece
-----------------------	--------------

Package Level 1 Width	0.1 mm
Package Level 1 Height	0.035 mm
Package Level 1 Depth / Length	0.1 mm
Package Level 1 Gross Weight	0.253 kg
Package Level 1 EAN	7320500474631

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Actuator Type	Flush
Bezel Material	Black Plastic
Color	Green
Connection Type	Screw Clamp
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Function	Momentary
Illumination	Illuminated
Mechanical Durability	0.5 million
Number of Auxiliary Contacts NO	1
Product Main Type	CP1
Product Name	Pushbutton
Rated Frequency (f)	50 / 60 Hz
Rated Operational Current AC-15 (I _e)	(220 / 240 V) 1 A
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Voltage	24 V AC/DC

Certificates and Declarations (Document Number)

CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Data Sheet, Technical Information	1SFC151007C02__
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2015-005451
DNV GL Certificate	9AKK107046A3749
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005451

Classifications

ETIM 6	EC001028 - Push button, complete
ETIM 7	EC001028 - Push button, complete
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

