

PRODUCT-DETAILS

CL2-623R

Compact Pilot Light Red LED 230V AC with 60V anti-inductive voltage



General Information

Extended Product Type	CL2-623R
Product ID	1SFA619403R6231
EAN	7320500556498
Catalog Description	Compact Pilot Light Red LED 230V AC with 60V anti-inductive voltage
Long Description	Compact Pilot Light - Pilot light head - Red - Illuminated - Lamptype: LED 230V AC with 60V anti-inductive voltage

Ordering

E-Number (Finland)	2313563
E-Number (Norway)	4373545
EAN	7320500556498
Minimum Order Quantity	10 piece
Customs Tariff Number	8536619090

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.052 m
Product Net Weight	0.1 kg

Container Information

Package Level 1 Units	bag 10 piece
Package Level 1 EAN	7320500510599

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Actuator Type	Pilot light head
Color	Red
Connection Type	Screw Clamp
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Illumination	Illuminated
Lamp Type	230 V AC, integrated LED
Product Main Type	CL2
Product Name	Pilot Light
Product Range	Compact
Rated Operational Voltage	230 V AC
RoHS Date	0635 4

Certificates and Declarations (Document Number)

CCC Certificate	2003010305054693_
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Data Sheet, Technical Information	1SFC151007C02_
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2015-005451
DNV GL Certificate	9AKK107046A3749
Environmental Information	1SFC151009D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005451

Classifications

ETIM 5	EC000272 - Indicator light complete
ETIM 6	EC000272 - Indicator light complete
ETIM 7	EC000272 - Indicator light complete
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.0 : 27371223

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

