

PRODUCT-DETAILS

AF140B-40-22RT-11

AF140B-40-22RT-11 Contactor



General Information

Extended Product Type	AF140B-40-22RT-11
Product ID	1SFL447262R1122
EAN	7320500509975
Catalog Description	AF140B-40-22RT-11 Contactor
Long Description	A 4-pole Contactor suitable for Railway applications such as Motor starting, Isolation, By-pass and Distribution application up to max 690 V. Operated with wide control voltage range 24-60 V, 50 and 60 Hz, 20-60 V DC

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0204
Instructions and Manuals	1SFC101065M0201

Dimensions

Product Net Width	120 mm
Product Net Depth /	128 mm

Length

Product Net Height	150 mm
Product Net Weight	1.95 kg

Technical

Number of Main Contacts NO	4
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 200 (690 V) 60 °C 175 A (690 V) 70 °C 160
Rated Operational Current AC-3 (I_e)	(415 V) 55 °C 140 A (440 V) 55 °C 140 A (380 / 400 V) 55 °C 140 A (220 / 230 / 240 V) 55 °C 140
Rated Short-time Withstand Current (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1168 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 477 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1460 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 674 A
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz / 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 5.5 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 5.5 V-A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 225 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 225 V-A Pull-in at Max. Rated Control Circuit Voltage DC 210 W
Terminal Type	Main Circuit: Bars

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	SEMKO_SE-70479M1
CCC Certificate	2013010304604055
CQC Certificate	CQC2013010304604055
cUL Certificate	20150602-E73397
cURus Certificate	20150602-E73397
Declaration of Conformity - CCC	2020980304001304
Declaration of Conformity - CE	2CMT2015-005440
EAC Certificate	9AKK107046A8618
Instructions and Manuals	1SFC101065M0201
RoHS Information	2CMT2015-005440

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	147 mm
Package Level 1 Depth / Length	197 mm
Package Level 1 Height	155 mm
Package Level 1 Gross Weight	2.15 kg
Package Level 1 EAN	7320500509975

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

