


PRODUCT-DETAILS

AFS146-30-12B-33

AFS146-30-12B-33



General Information

Extended Product Type	AFS146-30-12B-33
Product ID	1SFL467082R3312
EAN	7320500540527
Catalog Description	AFS146-30-12B-33
Long Description	A 3-phase Safety Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V. Operated with wide control voltage range 100-250 V, 50/60 Hz and DC with PLC control

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	1SFC100003M0201
--------------------------	-----------------

Dimensions

Product Net Width	90 mm
Product Net Depth / Length	126 mm

Product Net Height	150 mm
Product Net Weight	1.3 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	2
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 225 A
Rated Operational Current AC-1 (I_e)	(1000 V) 40 °C 225 A (1000 V) 60 °C 200 A (1000 V) 70 °C 175 A (690 V) 40 °C 225 A (690 V) 60 °C 200 A (690 V) 70 °C 175 A
Rated Operational Current AC-3 (I_e)	(415 V) 60 °C 146 A (440 V) 60 °C 146 A (500 V) 60 °C 130 A (690 V) 60 °C 93 A (1000 V) 60 °C 60 A (380 / 400 V) 60 °C 146 A (220 / 230 / 240 V) 60 °C 146 A
Rated Operational Power AC-3 (P_e)	(415 V) 75 kW (440 V) 90 kW (500 V) 90 kW (690 V) 90 kW (1000 V) 75 kW (380 / 400 V) 75 kW (220 / 230 / 240 V) 45 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 315 A
Rated Short-time Withstand Current (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1168 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 477 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1460 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 674 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 3000 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 1500 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 6 V·A

	Holding at Max. Rated Control Circuit Voltage 60 Hz 6 V-A Holding at Max. Rated Control Circuit Voltage DC 2.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 130 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 130 V-A Pull-in at Max. Rated Control Circuit Voltage DC 135 W
Operate Time	Between Coil De-energization and NO Contact Opening 37 ... 47 ms Between Coil Energization and NO Contact Closing 25 ... 55 ms
Connecting Capacity Main Circuit	Flexible 2 x 10 ... 70 mm² Rigid Cu-Cable 2 x 10 ... 95 mm²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm² Flexible 2x0.75 ... 2.5 mm² Solid 1 x 1 ... 4 mm² Stranded 2 x 1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 200 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 40 hp (220 ... 240 V AC) Three Phase 50 hp (440 ... 480 V AC) Three Phase 100 hp (550 ... 600 V AC) Three Phase 125 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... +50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +70 °C Close to Contactor for Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CB Certificate	SEMKO_SE-70479M1
CCC Certificate	2013010304604055
CQC Certificate	CQC2013010304604055
cUL Certificate	20120925-E36588
Declaration of Conformity - CCC	2020980304001304
Declaration of Conformity - CE	2CMT2018-005695
EAC Certificate	1SFC101360D1101
Instructions and Manuals	1SFC100003M0201
RoHS Information	2CMT2018-005695

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	207 mm
Package Level 1 Depth / Length	216 mm
Package Level 1 Height	150 mm
Package Level 1 Gross	1.5 kg

Weight	
Package Level 1 EAN	7320500540527

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

