

PRODUCT-DETAILS

GAF750-10-11-69

GAF750-10-11 48-130V 50/60Hz / 48-130V DC

Contactor



General Information

Extended Product Type	GAF750-10-11-69
Product ID	1SFL637025R6911
EAN	7320500400845
Catalog Description	GAF750-10-11 48-130V 50/60Hz / 48-130V DC Contactor
Long Description	A 3-pole Contactor suitable for DC-1 applications where all three poles must be connected in series in a 1-pole configuration up to max 1000 VDC. Operated with wide control voltage range 48-130 V, AC/DC

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC101045M9701
Dimension Diagram	53540919-60

Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	283 mm
Product Net Weight	14 kg

Technical

Number of Main Contacts NO	1
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 1050 A
Rated Operational Current DC-1 (I_e)	(1000 V) 3 Poles in Series, 40 °C 1050 A (1000 V) 3 Poles in Series, 55 °C 875 A (1000 V) 3 Poles in Series, 70 °C 720 A (220 V) 3 Poles in Series, 40 °C 1050 A (220 V) 3 Poles in Series, 55 °C 875 A (220 V) 3 Poles in Series, 70 °C 720 A (400 V) 3 Poles in Series, 40 °C 1050 A (400 V) 3 Poles in Series, 55 °C 875 A (400 V) 3 Poles in Series, 70 °C 720 A (600 V) 3 Poles in Series, 40 °C 1050 A (600 V) 3 Poles in Series, 55 °C 875 A (600 V) 3 Poles in Series, 70 °C 720 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	3 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 4.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 850 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 850 V·A Pull-in at Max. Rated Control Circuit Voltage DC 950 W
Connecting Capacity Main Circuit	Bar 52 mm ² Rigid Al-Cable 3x185 mm ² Rigid Cu-Cable 300 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(1000 V DC) 900 A (440 V DC) 900 A (600 V DC) 900 A

Environmental

Ambient Air Temperature	Operation -40 ... +80 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 K40 Shock Direction: B1 5 K40 Shock Direction: B2 5 K40 Shock Direction: C1 5 K40 Shock Direction: C2 5 K40
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CB Certificate	SEMKO_SE-70018
CCC Certificate	CQC_2013010304595900
CQC Certificate	CQC2013010304595900
cUL Certificate	20130524-E73397
Declaration of Conformity - CCC	2020980304001858
Declaration of Conformity - CE	2CMT003517
EAC Certificate	9AKK107046A8618
Environmental Information	1SFC101066D0201
Instructions and Manuals	1SFC101045M9701
RoHS Information	2CMT003517
UL Listing Card	UL_E73397

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7320500400845

Classifications		
Object Classification Code		Q
ETIM 4	EC002552 - Power contactor, DC switching	
ETIM 5	EC002552 - Power contactor, DC switching	
ETIM 6	EC002552 - Power contactor, DC switching	
ETIM 7	EC002552 - Power contactor, DC switching	
eClass	V11.0 : 27371018	
UNSPSC	39121529	
IDEA Granular Category Code (IGCC)	4763 >> Power contactor, DC switching	

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

