

## PRODUCT-DETAILS

# RBR121R-230VUC

RBR121R-230VUC Interface relay R600 1c/o,A1-A2=230VAC/DC,5-250VAC/60mA-6A, with integrated leakage current protection



## General Information

|                       |                                                                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | RBR121R-230VUC                                                                                                                                                               |
| Product ID            | 1SNA645511R2600                                                                                                                                                              |
| EAN                   | 4013614508257                                                                                                                                                                |
| Catalog Description   | RBR121R-230VUC Interface relay R600 1c/o,A1-A2=230VAC/DC,5-250VAC/60mA-6A, with integrated leakage current protection                                                        |
| Long Description      | Spring relay with leakage current protection RBR121R-230VUC: 230VAC/DC Rated control supply voltage/ 1 SPDT output contact rated 5-250VAC, 60mA up to 6A with integrated LED |

## Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 5 piece  |
| Customs Tariff Number  | 85364900 |

## Popular Downloads

|                                   |                    |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | 2CDC110004C0210_05 |
| Instructions and Manuals          | 1SVC645000M9000    |

## Dimensions

|                   |       |
|-------------------|-------|
| Product Net Width | 12 mm |
|-------------------|-------|

|                            |         |
|----------------------------|---------|
| Product Net Height         | 67.5 mm |
| Product Net Depth / Length | 75 mm   |
| Product Net Weight         | 0.04 kg |

## Technical

|                                                |                                                        |
|------------------------------------------------|--------------------------------------------------------|
| Function                                       | Boxed interface relay R600                             |
| Sub-Function                                   | Relay with built in LED and leakage current protection |
| Output                                         | 1 c/o (SPDT) contact                                   |
| Output Signal                                  | 5 ... 250VAC / 60mA ... 6A                             |
| Rated Control Supply Voltage (U <sub>s</sub> ) | 230 V AC/DC                                            |
| Terminal Type                                  | Spring Terminals                                       |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                 |                          |
|---------------------------------|--------------------------|
| CB Certificate                  | CB_DK-53188-UL           |
| CCC Certificate                 | CCC_2017010303941444     |
| CQC Certificate                 | CQC_2017010303941444     |
| CSA Certificate                 | CSA_254821               |
| cUR Certificate                 | cUR_E352056              |
| Declaration of Conformity - CCC | CCC_2020980303000254     |
| Declaration of Conformity - CE  | 1SVD982016-0001          |
| EAC Certificate                 | EAC_RU_C-FR.ME77.B.01634 |
| Instructions and Manuals        | 1SVC645000M9000          |
| LR Certificate                  | LR_16_20068              |
| RoHS Information                | 1SVD982016-0001          |
| UR Certificate                  | UR_E352056               |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 5 piece   |
| Package Level 1 Width          | 73 mm         |
| Package Level 1 Height         | 71 mm         |
| Package Level 1 Depth / Length | 80 mm         |
| Package Level 1 Gross Weight   | 0.24 kg       |
| Package Level 1 EAN            | 3472596455118 |

## Classifications

|                            |                            |
|----------------------------|----------------------------|
| Object Classification Code | K                          |
| ETIM 4                     | EC001437 - Switching relay |
| ETIM 5                     | EC001437 - Switching relay |
| ETIM 6                     | EC001437 - Switching relay |
| ETIM 7                     | EC001437 - Switching relay |

|                   |                  |
|-------------------|------------------|
| eClass            | V11.0 : 27371601 |
| UNSPSC            | 39122331         |
| E-Number (Sweden) | 4001156          |

---

**Categories**

---

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

