

PRODUCT-DETAILS

CP-C.1-A-RU-C

CP-C.1-A-RU-C Redundancy unit for power supplies In: 2x20A, Out: 1x40A



General Information

Extended Product Type	CP-C.1-A-RU-C
Product ID	1SVR360060R2001
EAN	4013614523748
Catalog Description	CP-C.1-A-RU-C Redundancy unit for power supplies In: 2x20A, Out: 1x40A
Long Description	The CP-C.1-A-RU-C is a redundancy unit for CP-C.1 range power supplies. This unit, with 2 inputs / channels each up to 20 A and an output up to 40 A, provides true redundancy by 100 % decoupling of two parallel connected CP-C.1 range power supplies.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044082

Popular Downloads

Data Sheet, Technical Information	2CDC114103D0201
Instructions and Manuals	1SVC360561M0000
Instructions and Manuals (Part 2)	1SVC360560M9000

Dimensions

Product Net Width	56.4 mm
Product Net Height	129.4 mm
Product Net Depth / Length	136 mm
Product Net Weight	1.04 kg

Container Information

Package Level 1 Width	90 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Height	165 mm
Package Level 1 Gross Weight	1.17 kg
Package Level 1 EAN	4013614523748
Package Level 1 Units	box 1 piece

Technical

Function	Redundancy unit
Rated Input Voltage (U_{IN})	12 ... 48 V DC
Input Voltage (U_{in})	10 ... 58 V DC
Rated Output Voltage	12 ... 48 V DC
Output Voltage (U_{out})	10 ... 58 V DC
Rated Output Current	40 A
Output Current	60 A
Degree of Protection	Housing IP20 Terminals IP20
Pollution Degree	2
Connecting Capacity Input Circuit	Flexible with Ferrule 2.5 ... 10 mm ² Flexible 2.5 ... 10 mm ² Rigid 2.5 ... 16 mm ²
Connecting Capacity Output Circuit	Flexible with Ferrule 2.5 ... 10 mm ² Flexible 2.5 ... 10 mm ² Rigid 2.5 ... 16 mm ²
Tightening Torque	Input Circuit 1.2 N·m Output Circuit 1.2 N·m
Wire Stripping Length	Input Circuit 10 mm Output Circuit 10 mm
Recommended Screw Driver	Input Circuit / Output Circuit 0.8 x 4 Input Circuit / Output Circuit PH1
Mounting Position	Position 1, 7
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Standards	EN 50581 IEC/EN 60079-0 IEC/EN 60079-7 IEC/EN 61000-6-2 IEC/EN 61000-6-3 IEC/EN 61204 UL 61010-2-201 UL 61010-1 IEC/EN 61010-1

Environmental

Ambient Air Temperature	Operation -40 ... +70 °C Storage -40 ... +85 °C
-------------------------	--

Resistance to Vibrations acc. to IEC 60068-2-6	10-58 Hz, ± 0.15 mm; 58-150 Hz, 2g, 10 sweep cycles each axis
Resistance to Shock acc. to IEC 60068-2-27	30g / 3 shocks / 6 ms
Resistance to Damp Heat acc. to IEC 60068-2 -30	Test Db: 55°C, 2 cycles
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Connecting Capacity	Flexible 12-8 AWG
Input Circuit UL/CSA	Rigid 12-6 AWG
Connecting Capacity	Flexible 12-8 AWG
Output Circuit UL/CSA	Rigid 12-6 AWG

Electromagnetic Compatibility

Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV
Electromagnetic Compatibility (EMC)	Immunity - Class B Emission - Class B

Certificates and Declarations (Document Number)

ABS Certificate	ABS_17-HG1661393-1-PDA
ATEX Certificate	Type Examination Certificate_DEMKO_16_ATEX_1746X
CB Certificate	CB_DK-65060-M1-UL
cULus Certificate	cULus508_20170703-E174460
cURus Certificate	cURus60950_E196145-A12-UL; cURusANSI-12-12_20170825_E317914
Declaration of Conformity - CE	1SVD982029
DNV GL Certificate	DNV_GL_TAA00001C0_1
Instructions and Manuals	1SVC360561M0000
Instructions and Manuals (Part 2)	1SVC360560M9000
RoHS Information	1SVD982029

Classifications

Object Classification Code	T
ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
eClass	V11.0 : 27040701
UNSPSC	39121004
E-Number (Finland)	2712559

Categories

Low Voltage Products and Systems → Control Products → Power Supplies

