

PRODUCT-DETAILS

CP-C.1-A-RU-L

CP-C.1-A-RU-L Redundancy unit for power supplies In: 2x20A, Out: 1x40A



General Information

Extended Product Type	CP-C.1-A-RU-L
Product ID	1SVR361060R1001
EAN	4053546028140
Catalog Description	CP-C.1-A-RU-L Redundancy unit for power supplies In: 2x20A, Out: 1x40A
Long Description	CP-C.1-A-RU-L Redundancy unit for power supplies In: 2x20A, Out: 1x40A

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

Popular Downloads

Data Sheet, Technical Information	2CDC114103D0201
Instructions and Manuals	1SVC360561M0000

Dimensions

Product Net Width	56.4 mm
Product Net Height	129.4 mm
Product Net Depth /	136 mm

Length

Product Net Weight	1.04 kg
--------------------	---------

Container Information

Package Level 1 Width	90 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Height	165 mm
Package Level 1 Gross Weight	1.17 kg
Package Level 1 EAN	4053546028140
Package Level 1 Units	box 1 piece

Technical

Function	Redundancy unit
Rated Input Voltage (U _{IN})	12 ... 48 V DC
Input Voltage (U _{in})	10 ... 58 V DC
Rated Output Voltage	12 ... 48 V DC
Output Voltage (U _{out})	10 ... 58 V DC
Rated Output Current	40 A
Degree of Protection	Housing IP20 Terminals IP20
Pollution Degree	2
Connecting Capacity Input Circuit	Flexible with Ferrule 2.5 ... 10 mm ² Flexible 2.5 ... 10 mm ² Rigid 2.5 ... 16 mm ²
Connecting Capacity Output Circuit	Flexible with Ferrule 2.5 ... 10 mm ² Flexible 2.5 ... 10 mm ² Rigid 2.5 ... 16 mm ²
Tightening Torque	Input Circuit 1.2 N·m Output Circuit 1.2 N·m
Wire Stripping Length	Input Circuit 10 mm Output Circuit 10 mm
Recommended Screw Driver	Input Circuit / Output Circuit 0.8 x 4 Input Circuit / Output Circuit PH1
Mounting Position	Position 1, 7
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Standards	EN 50581 IEC/EN 61000-6-2 IEC/EN 61000-6-3 IEC/EN 61204 UL 61010-2-201 UL 61010-1 IEC/EN 61010-1

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Resistance to Vibrations acc. to IEC 60068-2-6	10-58 Hz, ±0.15 mm; 58-150 Hz, 2g, 10 sweep cycles each axis
Resistance to Shock acc. to IEC 60068-2-27	30g / 3 shocks / 6 ms
Resistance to Damp Heat acc. to IEC 60068-2-30	Test Db: 55°C, 2 cycles
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Connecting Capacity	Flexible 12-8 AWG
Input Circuit UL/CSA	Rigid 12-6 AWG
Connecting Capacity	Flexible 12-8 AWG
Output Circuit UL/CSA	Rigid 12-6 AWG

Electromagnetic Compatibility

Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV
Electromagnetic Compatibility (EMC)	Immunity - Class B Emission - Class B

Certificates and Declarations (Document Number)

ABS Certificate	ABS_17-HG1661393-1-PDA
CB Certificate	CB_DK-65060-M1-UL
cULus Certificate	cULus508_20170703-E174460
cURus Certificate	cURus60950_E196145-A12-UL; cURusANSI-12-12_20170825_E317914
Declaration of Conformity - CE	1SVD982027
DNV GL Certificate	DNV_GL_TAA00001C0_1
EAC Certificate	EAC_RU_C-DE.ME77.B.02880
Instructions and Manuals	1SVC360561M0000
RoHS Information	1SVD982027

Classifications

Object Classification Code	T
ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
eClass	V11.0 : 27040701
UNSPSC	39121004

Categories

Low Voltage Products and Systems → Control Products → Power Supplies

