

PRODUCT-DETAILS

CP-C.1 24/20.0-L

CP-C.1 24/20.0-L Power supply In:100-240VAC/90-300VDC Out:DC 24V/20A



General Information

Extended Product Type	CP-C.1 24/20.0-L
Product ID	1SVR361763R1001
EAN	4053546028133
Catalog Description	CP-C.1 24/20.0-L Power supply In:100-240VAC/90-300VDC Out:DC 24V/20A
Long Description	CP-C.1 24/20.0-L Power supply In:100-240VAC/90-300VDC Out:DC 24V/20A

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

Popular Downloads

Data Sheet, Technical Information	2CDC114106D0201
Instructions and Manuals	1SVC360560M0000

Dimensions

Product Net Width	82 mm
Product Net Height	129.4 mm
Product Net Depth /	136 mm

Length

Product Net Weight	1.57 kg
--------------------	---------

Container Information

Package Level 1 Width	110 mm
Package Level 1 Depth / Length	168 mm
Package Level 1 Height	160 mm
Package Level 1 Gross Weight	1.7 kg
Package Level 1 EAN	4053546028133
Package Level 1 Units	box 1 piece

Technical

Function	Switch mode power supply
Number of Phases	1
Rated Input Voltage (U_{IN})	100 ... 240 V AC 90 ... 300 V DC
Input Voltage (U_{in})	85 ... 264 V AC 90 ... 300 V DC
Typical Input Current	(115 V AC) 4.6 A (230 V AC) 2.3 A
Hold-up Time	(230 V AC) min. 40 ms
Rated Frequency (f)	50 Hz 60 Hz
Rated Frequency Limits	45 ... 65 Hz
Characteristic of Output	U/I characteristic curve with power reserve
Rated Output Power	480 W
Output Power	480 W
Rated Output Voltage	24 V DC
Output Voltage (U_{out})	24 V DC
Rated Output Current	-25 °C ... +40 °C 26 A -25 °C ... +60 °C 20 A
Output Current	20 A
Output Current Maximum (I_{out})	26 A
Rated Impulse Withstand Voltage (U_{imp})	Input Circuit / Output Circuit 4 kV Input Circuit / PE 4 kV Input Circuit / Relay Contact 4 kV Output Circuit / PE 0.5 kV Output Circuit 0.5 kV
Rated Insulation Voltage (U_i)	Input Circuit / Output Circuit 300 V Input Circuit / PE 300 V Input Circuit / Relay Contact 300 V Output Circuit / PE 50 V
Degree of Protection	Housing IP20 Terminals IP20
Pollution Degree	2
Connecting Capacity Input Circuit	Flexible with Ferrule 0.5 ... 2.5 mm ² Flexible 0.5 ... 2.5 mm ² Rigid 0.5 ... 4 mm ²
Connecting Capacity Output Circuit	Flexible with Ferrule 2.5 ... 10 mm ² Flexible 2.5 ... 10 mm ² Rigid 2.5 ... 16 mm ²
Tightening Torque	Auxiliary Circuit 0.5 N·m Input Circuit 0.5 N·m Output Circuit 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 8 mm Input Circuit 8 mm Output Circuit 10 mm

Recommended Screw Driver	Input Circuit / Output Circuit PH1 Input Circuit / Output Circuit 0.8 x 4
Minimum Mounting Distance	Electrical Conductive Board, Horizontal 25 mm Electrical Conductive Board, Vertical 25 mm Other Device Same Type, Horizontal 25 mm Other Device Same Type, Vertical 25 mm
Mounting Position	Position 1, 7
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.107.1 EN 50581 IEC/EN 61000-6-2 IEC/EN 61000-6-3 IEC/EN 61204 UL 508 IEC/EN 61010-1 UL 61010-1 UL 61010-2-201

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Resistance to Vibrations acc. to IEC 60068-2-6	10-58 Hz, ±0.15 mm; 58-150 Hz, 2g, 10 sweep cycles each axis
Resistance to Shock acc. to IEC 60068-2-27	30g / 3 shocks / 6 ms
Resistance to Damp Heat acc. to IEC 60068-2-30	Test Db: 55°C, 2 cycles
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Connecting Capacity Input Circuit UL/CSA	Flexible with Ferrule 20-12 AWG Flexible 20-12 AWG Rigid 20-10 AWG
Connecting Capacity Output Circuit UL/CSA	Flexible 12-8 AWG Rigid 12-6 AWG
Tightening Torque UL/CSA	Input Circuit 4.4 in-lb Output Circuit 10.5 in-lb

Electromagnetic Compatibility

Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV
Radiated Electromagnetic Field Immunity acc. to IEC 61000-4-3	Level 3 10 V/m
Electrical Fast Transient (Burst Immunity) acc. to IEC 61000-4-4	Level 4 Power Supply Port Signal 4 kV
Surge Immunity acc. to IEC 61000-4-5	Level 4 Line-to-Ground 4 kV Level 4 Line-to-Line 2 kV
Conducted Disturbances Immunity acc. to IEC 61000-4-6	Level 3 10 V
Electromagnetic Compatibility (EMC)	Immunity - Class B Emission - Class B

Certificates and Declarations (Document Number)	
ABS Certificate	ABS_17-HG1591548-2-PDA
CB Certificate	CB_DK-59135-A3-UL
cULus Certificate	cULus508_20161102-E174460
cURus Certificate	cURus60950_E196145-A11-UL; cURusANSI-12-12_20161122_E317914
Declaration of Conformity - CE	1SVD982010
DNV GL Certificate	DNV_GL_TAA00000YB_1
EAC Certificate	EAC_RU_C-DE.ME77.B.02550
Instructions and Manuals	1SVC360560M0000
RoHS Information	1SVD982010

Classifications	
Object Classification Code	T
ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
eClass	V11.0 : 27040701
UNSPSC	39121004

Categories

Low Voltage Products and Systems → Control Products → Power Supplies

