

PRODUCT-DETAILS

CR-P048AC1

CR-P048AC1 Pluggable interface relay 1c/o, A1 -A2=48VAC, 250V/16A



| General Information | |
|-----------------------|--|
| Extended Product Type | CR-P048AC1 |
| Product ID | 1SVR405600R5000 |
| EAN | 4013614498183 |
| Catalog Description | CR-P048AC1 Pluggable interface relay 1c/o, A1-A2=48VAC, 250V/16A |
| Long Description | The CR-P048AC1 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 48 V AC rated control supply voltage and has a 1 c/o (SPDT) output contact rated at 250 V / 16 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

| | modules, noider and marker are available as accessories. |
|-----------------------------------|--|
| | |
| Ordering | |
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85364900 |
| Popular Downloads | |
| Data Sheet, Technical Information | 2CDC110004C0210_05 |
| Instructions and | 1SVC405600M9000 |

| Dimensions | |
|-------------------|---------|
| Product Net Width | 12.7 mm |

| Product Net Height | 15.7 mm |
|-------------------------------|----------|
| Product Net Depth / Length | 29 mm |
| Product Net Weight | 0.014 kg |

| Technical | hnical | |
|--|------------------------------------|--|
| Function | Pluggable pcb interface relay CR-P | |
| Sub-Function | Relay w/o built in LED | |
| Output | 1 c/o (SPDT) contact | |
| Output Signal | 250 V / 16 A | |
| Rated Control Supply Voltage (U _s) | 48 V AC | |

| Environmental | |
|---------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |

| Certificates and Declarations (Document Number) | |
|---|-----------------------------|
| CCC Certificate | CCC_2007010303228779 |
| CSA Certificate | CSA_1587291 |
| cUR Certificate | cUR_E244330 |
| Declaration of Conformity - CCC | 2020970303000496 |
| Declaration of Conformity - CE | No declaration needed |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD982031-0000 |
| UR Certificate | UR_E244330 |
| VDE Certificate | VDE_40019129 |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 332 mm |
| Package Level 1 Height | 28 mm |
| Package Level 1 Depth / Length | 17 mm |
| Package Level 1 Gross Weight | 0.157 kg |
| Package Level 1 EAN | 4013614372926 |

| Classifications | |
|-------------------------------|----------------------------|
| Object Classification Code | К |
| ETIM 4 | EC001437 - Switching relay |
| ETIM 5 | EC001437 - Switching relay |
| ETIM 6 | EC001437 - Switching relay |
| ETIM 7 | EC001437 - Switching relay |

CR-P048AC1 3

| eClass | V11.0 : 27371601 |
|--------------------|------------------|
| UNSPSC | 39122331 |
| E-Number (Finland) | 2712742 |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Electronic\ Relays\ and\ Controls \rightarrow Interface\ Relays\ and\ Optocouplers$

