

PRODUCT-DETAILS

CR-U120AC2

CR-U120AC2 Pluggable interface relay 2c/o, A1 -A2=120VAC, 250V/10A



| General Information | |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CR-U120AC2 |
| Product ID | 1SVR405621R2000 |
| EAN | 4013614498398 |
| Catalog Description | CR-U120AC2 Pluggable interface relay 2c/o, A1-A2=120VAC, 250V/10A |
| Long Description | The CR-U120AC2 pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 120 V AC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories. |

| 10 piece |
|----------|
| 85364900 |
| |

| Popular Downloads | |
|--------------------------------------|--------------------|
| Data Sheet, Technical Information | 2CDC110004C0210_05 |
| Instructions and Manuals | 1SVC405600M9000 |

Dimensions

| Product Net Width | 35 mm |
|-------------------------------|----------|
| Product Net Height | 54.4 mm |
| Product Net Depth / Length | 35 mm |
| Product Net Weight | 0.083 kg |

| Technical | |
|---------------------------------------------------|------------------------------------------|
| Function | Pluggable universal interface relay CR-U |
| Sub-Function | Relay w/o built in LED |
| Output | 2 c/o (SPDT) contacts |
| Output Signal | 250 V / 10 A |
| Rated Control Supply Voltage (U _s) | 120 V AC |

| Environmental | |
|---------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |

| CCC Certificate | CCC_2017010303949759 |
|------------------------------------|-----------------------------|
| CQC Certificate | CQC2017010303949759 |
| CSA Certificate | CSA_1587291 |
| Declaration of Conformity - CCC | 2020980303000199 |
| Declaration of Conformity - CE | 1SVD982021-0003 |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| LR Certificate | LR_05_20002_E5 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD982021-0003 |
| UR Certificate | UR_E244330 |
| VDE Certificate | VDE 40019116 |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 182 mm |
| Package Level 1 Height | 76 mm |
| Package Level 1 Depth / Length | 77 mm |
| Package Level 1 Gross Weight | 0.87 kg |
| Package Level 1 EAN | 4013614374067 |

| Classifications | |
|-------------------------------|----------------------------|
| Object Classification Code | К |
| ETIM 4 | EC001437 - Switching relay |
| ETIM 5 | EC001437 - Switching relay |

CR-U120AC2 3

| ETIM 6 | EC001437 - Switching relay |
|--------------------|----------------------------|
| ETIM 7 | EC001437 - Switching relay |
| eClass | V11.0 : 27371601 |
| UNSPSC | 39122331 |
| E-Number (Finland) | 2712787 |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Electronic\ Relays\ and\ Controls \rightarrow Interface\ Relays\ and\ Optocouplers$

