

PRODUCT-DETAILS

CR-U048DC3L

CR-U048DC3L Pluggable interface relay 3c/o, A1-A2=48VDC, 250V/10A, LED



| General Information | |
|-----------------------|--|
| Extended Product Type | |
| Product ID | |
| FANI | |

EAN 4013614498695
Catalog Description CR-U048DC3L Pluggable interface relay 3c/o, A1-A2=48VDC, 250V/10A, LED

Long Description

The CR-U048DC3L pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 48 V DC rated control supply voltage and has 3 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

CR-U048DC3L 1SVR405622R6100

Ordering

| Minimum Order Quantity | 10 piece |
|------------------------|----------|
| Customs Tariff Number | 85364900 |

Popular Downloads

| Data Sheet, Technical Information | 2CDC110004C0210_05 |
|--------------------------------------|--------------------|
| Instructions and | 1SVC405600M9000 |
| Manuals | |

Dimensions

| Product Net Width | 35 mm |
|-------------------------------|----------|
| Product Net Height | 54.4 mm |
| Product Net Depth / Length | 35 mm |
| Product Net Weight | 0.083 kg |

| Technical | |
|---|--|
| Function | Pluggable universal interface relay CR-U |
| Sub-Function | Relay with built in LED |
| Output | 3 c/o (SPDT) contacts |
| Output Signal | 250 V / 10 A |
| Rated Control Supply Voltage (U _s) | 48 V DC |

Environmental RoHS Status Following EU Directive 2011/65/EU

| Certificates and Declarations (Document Number) | |
|---|-----------------------------|
| CCC Certificate | CCC_2017010303949759 |
| CQC Certificate | CQC2017010303949759 |
| CSA Certificate | CSA_1587291 |
| Declaration of Conformity - CCC | 2020980303000199 |
| Declaration of Conformity - CE | 1SVD982021-0003 |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| LR Certificate | LR_05_20002_E5 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD982021-0003 |
| UR Certificate | UR_E244330 |
| VDE Certificate | VDE_40019116 |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 182 mm |
| Package Level 1 Height | 76 mm |
| Package Level 1 Depth / Length | 77 mm |
| Package Level 1 Gross Weight | 0.87 kg |
| Package Level 1 EAN | 4013614374302 |

| Classifications | |
|-------------------------------|----------------------------|
| Object Classification Code | К |
| ETIM 4 | EC001437 - Switching relay |
| ETIM 5 | EC001437 - Switching relay |

CR-U048DC3L 3

| ETIM 6 | EC001437 - Switching relay |
|--------------------|----------------------------|
| ETIM 7 | EC001437 - Switching relay |
| eClass | V11.0 : 27371601 |
| UNSPSC | 39122331 |
| E-Number (Finland) | 2712778 |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Electronic\ Relays\ and\ Controls \rightarrow Interface\ Relays\ and\ Optocouplers$

